K-19



DeviceNet Series MDC Receptacles

5 Conductor DeviceNet Series MDC Receptacles, 22 & 24AWG



Front & Back Mount Receptacles with Drop Cable

300 Volt, 4 amps


IP67 Rating




Front Mount Receptacles with Drop Cable - 1/2" NPT						
# of Poles	Male Faceview	Color Code	Rating	Wire AWG	Male Receptacle	Female Receptacle
5	20 30 0 ⁵ 01 0 ₄ M12 x 1	1. Bare (Drain) 2. Red (V+) 3. Black (V-) 4. White (CAN_H) 5. Blue (CAN_L)	300V 4A	22 & 24 AWG	MDCDD-5MR-2-**	MDCDD-5FR-2-**
Back Mount Receptacles with Drop Cable						
5	2 ₀ 30 0 ⁵ 01 0 ₄ M12 x 1	1. Bare (Drain) 2. Red (V+) 3. Black (V-) 4. White (CAN_H) 5. Blue (CAN_L)	300V 4A	22 & 24 AWG	MDCDD-5MR-BM-**	MDCDD-5FR-BM-**

^{**} Lengths in meters.

Standard Receptacles with Drop Cables



Male Receptacles



Back Mount Receptacles with Drop Cables

