# Product data sheet Characteristics

# HU266AWK

Safety switch, heavy duty, non fusible, 600A, 2 poles, 400 hp, 600 VAC/DC, NEMA 12

Product availability: Non-Stock - Not normally stocked in distribution facility





Price\*: 8,112.00 USD



#### Main

IVIAIII		
Product	Single Throw Safety Switch	
Duty Rating	Heavy duty	
Device application	Heavy application	,
Disconnect Type	Non-fusible disconnect	
Factory Installed Neutral	None	
Phase	3 phase	
Number of Poles	2	
Current Rating	600 A	
Voltage Rating	600 V AC/DC	
Enclosure Rating	NEMA 3R/12 galvannealed steel	
Maximum Horse Power Rating	200 hp 240 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 400 hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 50 hp 250 V at DC 50 hp 600 V at DC	

#### Complementary

Mounting Type	Surface	
Electrical Connection	Lugs	
Wiring configuration	2-wire	
Wire Size	AWG 3/0500 kcmil copper or aluminium	in en in
Tightening torque	375 lbf.in (42.37 N.m) (AWG 3/0500 kcmil)	
Depth	10.13 in (257.30 mm)	oo <del>t</del>
Width	26.25 in (666.75 mm)	an a
Height	46.25 in (1174.75 mm)	
Net Weight	169.98 lb(US) (77.1 kg)	

<sup>\*</sup> Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

## Environment

0 (' (' ('	LII 15-15-1 CI- E007E	
Certifications	UL listed file E2875	
Ochanodaorio	OL HOLOG IIIO LEGITO	

## Ordering and shipping details

Category	00155 - H&HU SW,NEMA12,400-1200A
Discount Schedule	DE1
GTIN	00785901451310
Nbr. of units in pkg.	1
Package weight(Lbs)	170.00 lb(US) (77.111 kg)
Returnability	No
Country of origin	US

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	18.21 in (46.251 cm)
Package 1 width	3.99 in (10.13 cm)
Package 1 Length	10.34 in (26.251 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.	
Environmental Disclosure	Product Environmental Profile	
PVC free	Yes	
Halogen content performance	Halogen free plastic parts product	

## Contractual warranty

Warranty	18 months	