



# 7/8" MIN Series Size I Receptacles

2, 3, 4, 5 & 6 Conductor MIN Series Size I Receptacles













Male-Female Through Panel Mount Receptacles | IP69 Rating



A

MIN Series Size I Receptacles

| # of Poles | Male Faceview                                                                                     | Rating      | Part Number  | Wiring                                                   | Female Faceview                                                                                     |
|------------|---------------------------------------------------------------------------------------------------|-------------|--------------|----------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| 2          | <br>7/8"-16UN2   | 600V<br>13A | MIN-2MFRF-TM | 1 to 1<br>2 to 2                                         | <br>7/8"-16UN2   |
| 3          | <br>7/8"-16UN2   | 600V<br>13A | MIN-3MFRF-TM | 1 to 1<br>2 to 2<br>3 to 3                               | <br>7/8"-16UN2   |
| 4          | <br>7/8"-16UN2   | 600V<br>10A | MIN-4MFRF-TM | 1 to 1<br>2 to 2<br>3 to 3<br>4 to 4                     | <br>7/8"-16UN2   |
| 5          | <br>7/8"-16UN2 | 600V<br>8A  | MIN-5MFRF-TM | 1 to 1<br>2 to 2<br>3 to 3<br>4 to 4<br>5 to 5           | <br>7/8"-16UN2 |
| 6          | <br>7/8"-16UN2 | 600V<br>8A  | MIN-6MFRF-TM | 1 to 1<br>2 to 2<br>3 to 3<br>4 to 4<br>5 to 5<br>6 to 6 | <br>7/8"-16UN2 |

## Specifications:

|                 |                                  |
|-----------------|----------------------------------|
| Shell:          | Nickel Plated Brass              |
| Insulator:      | 105°C, Oil Resistant Yellow PVC  |
| Contacts:       | Copper Alloy with Gold Plating   |
| Jam Nut:        | Nickel Plated Brass              |
| Thrust Washer:  | Zinc Die-Cast                    |
| Sealing Washer: | NBR                              |
| Temperature:    | -40°C to 105°C (-40°F to +221°F) |

