



1 3/8" MIN Power Series Receptacles




3, 4 & 5 Conductor PMIN Receptacles, 10, 12 & 14AWG



Front Mount Receptacles | 1/2"-14 NPT Threads | IP67 Rating


5 pole is not UL listed.




# of Poles	Male Faceview	Color Code	Rating	Wire AWG	Male Receptacles	Female Receptacles
3	 1.375"-16UN2	North American 1. Black 2. Green/Yellow 3. White	600V 35A	10 AWG	PMIN-30MR-**	PMIN-30FR-**
			600V 28A	12 AWG	PMIN-32MR-**	PMIN-32FR-**
			600V 24A	14 AWG	PMIN-34MR-**	PMIN-34FR-**
4	 1.375"-16UN2	North American 1. Black 2. Green/Yellow 3. Red 4. White	600V 32A	10 AWG	PMIN-40MR-**	PMIN-40FR-**
			600V 25A	12 AWG	PMIN-42MR-**	PMIN-42FR-**
			600V 20A	14 AWG	PMIN-44MR-**	PMIN-44FR-**
5	 1.375"-16UN2	North American 1. Black 2. Green/Yellow 3. Red 4. White 5. Gray	600V 25A	10 AWG	PMIN-450MR-**	PMIN-450FR-**

D
PMIN Receptacles

** Lengths in meters. 0.3m leads are standard. Longer lead lengths are available, please consult the factory for part numbers.



Male Receptacles



Female Receptacles

Specifications:

Shell: Nickel Plated Brass
Insulator: 105°C, Oil Resistant Black PVC
Wire: 10 AWG: UL Style 1015, 600V
12 AWG: UL Style 1015, 600V
14 AWG: UL Style 1015, 600V

Contacts: Copper Alloy with Gold Plating
Gasket: TPE
Lock Nut: Zinc Plated Steel
Temperature: -40°C to 90°C (-40°F to +194°F)