



PIN #	COLOR
1	BLACK
2	GREEN / YELLOW
3	WHITE



MATERIALS	
BODY:	BLACK PVC
INSERT:	BLACK PVC
CONTACTS:	GOLD PLATED COPPER ALLOY
CABLE:	12/3 TC-ER FT4 BLK TPE JKT
COUPLING:	NICKEL PLATED BRASS

RATINGS:	
SCCR RATING:	65kA Breakers and Fuses
RoHS COMPLIANT:	Yes
PROTECTION:	IP67
UL CATEGORY:	PVVA (US), PVVA7 (Canada)
U.S.	UL 2237 LISTED, File E469485
CANADA	C-UL 2237 LISTED, File E469485

CAUTION:

RISK OF ELECTRICAL SHOCK

DO NOT DISCONNECT UNDER LOAD

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.

VOLTS	600V
AMPS	28A
TEMP:	-40° to 90°C

UNLESS OTHERWISE SPECIFIED:	DRAWN BY	ADM
DIMENSIONS ARE IN INCHES AND [MM]	DRAWN DATE	06/22/2020
	CHECKED BY	GO
	CHECK DATE	06/23/2020
MATERIAL	COMMENTS:	
FINISH		
DO NOT SCALE DRAWING		

P/N	L	STD?
PMINW-32FP-1M-C011	40" [1m]	YES
PMINW-32FP-2M-C011	79" [2m]	YES
PMINW-32FP-3M-C011	117" [3m]	YES
PMINW-32FP-4M-C011	157" [4m]	YES
PMINW-32FP-5M-C011	197" [5m]	YES
PMINW-32FP-6M-C011	236" [6m]	NO
PMINW-32FP-8M-C011	315" [8m]	NO
PMINW-32FP-10M-C011	393" [10m]	YES
PMINW-32FP-15M-C011	590" [15m]	YES
PMINW-32FP-20M-C011	787" [20M]	YES

PARTS LISTED AS NOT BEING STANDARD
MAY REQUIRE MINIMUM ORDERS
OTHER LENGTHS AVAILABLE,
PLEASE CONSULT FACTORY

MENCOM CORPORATION		
TITLE:		
3 PL FEM PLG PMIN 12AWG		
SIZE	DWG. NO.	REV
B	PMINW-32FP-ZZ-C011	B
SCALE: 1:1	WEIGHT:	SHEET 1 OF 1