

HPS CAT NO.	1	2	3	APPLICATION RANGE
	APPLIED LENGTH	NECK SIZE	CONDUCTOR COLOR	
LDID0004	13	"C" - BLACK & "F" - YELLOW	ORANGE	0.245 TO 0.277 IN (6.22 TO 7.05 mm)
LDID0001	14	"C" - BLACK & "F" - YELLOW	RED	0.316 TO 0.357 IN (8.03 TO 9.07 mm)
LDID0010	14	"C" - BLACK & "F" - YELLOW	YELLOW	0.358 TO 0.405 IN (9.09 TO 10.30 mm)
LDID0020	15	"C" - BLACK & "F" - YELLOW	BLUE	0.406 TO 0.459 IN (10.31 TO 11.66mm)
LDID0030	16	"C" - BLACK & "F" - YELLOW	ORANGE	0.460 TO 0.520 IN (11.68 TO 13.21mm)
LDID0040	17	"C" - BLACK & "F" - YELLOW	RED	0.521 TO 0.588 IN (13.23 TO 14.95 mm)
LDID0266	17	"C" - BLACK & "F" - YELLOW	PURPLE	0.589TO 0.665 IN (14.96 TO 16.89mm)
LDID0336	18	"C" - BLACK & "F" - YELLOW	BROWN	0.666 TO 0.755 IN (16.91 TO 19.18 mm)
LDID0477	20	"C" - BLACK & "F" - YELLOW	RED	0.756 TO 0.855 IN (19.20 TO 21.73 mm)
LDID0556	21	"C" - BLACK & "F" - YELLOW	BLUE	0.856 TO 0.968 IN (21.74 TO 24.60 mm)
LDID0795	22	"C" - BLACK & "F" - YELLOW	GREEN	0.969 TO 1.096 IN (24.61 TO 27.84 mm)
LDID2004	14	"J" -GREEN	ORANGE	0.245 TO 0.277 IN (6.22 TO 7.04 mm)
LDID2003	14	"J" -GREEN	PURPLE	0.278 TO 0.315 IN (7.06 TO 8.00mm)
LDID2001	15	"J" -GREEN	RED	0.316 TO 0.357 IN (8.02 TO 9.07 mm)
LDID2010	15	"J" -GREEN	YELLOW	0.358 TO 0.405 IN (9.09 TO 10.29 mm)
LDID2020	16	"J" -GREEN	BLUE	0.406 TO 0.459 IN (10.31 TO 11.66mm)
LDID2030	16	"J" -GREEN	ORANGE	0.460 TO 0.520 IN (11.68 TO 13.21mm)
LDID2040	18	"J" -GREEN	RED	0.521 TO 0.588 IN (13.23 TO 14.94 mm)
LDID2266	18	"J" -GREEN	PURPLE	0.589 TO 0.665 IN (14.96 TO 16.89mm)
LDID2336	19	"J" -GREEN	BROWN	0.666 TO 0.755 IN (16.92 TO 19.18 mm)
LDID2477	21	"J" -GREEN	RED	0.756 TO 0.855 IN (19.20 TO 21.72 mm)
LDID2556	22	"J" -GREEN	BLUE	0.856 TO 0.968 IN (21.74 TO 24.59 mm)
LDID2795	23	"J" -GREEN	GREEN	0.969 TO 1.096 IN (24.61 TO 27.84 mm)

NOTES:

- ALUMINUM.
- 2. DIMENSIONS: INCHES (MILLIMETERS).
- 3. HAND LAY STANDARD DIRECTION: RIGHT.
- INSULATORS SHOULD BE PER ANSI C29.3, C29.5 C29.6 AND C29.7. NECK DIAMETERS: 2-1/4" OR 2-7/8".

