

YS32FXB

by Burndy
Catalog ID: YS32FXB

Prop 65 Notice

Copper Compression Splice, 313.1 kcmil, 4.82" Splice Length, Long barrel, belled end, Tin Plated



Product Details

General

Color Code	Red
Connector Type	Splice
Die Index	18
Feature - Barrel Style	Belled
Feature - Barrel Type	Long
Material	Copper
Plated	Y
Plating Type	Tin - Electro Plated
Temperature Rating	194
Trade Name	HYLINK™
UPC	781810041529
UPC 12 Digit	7818100415299

Dimensions

Dimension - B Length inch	2.32 in
Dimension - D inch	1.12 in
Dimension - L Length Overall mm	122 mm
Dimension - Length Overall inch	4.82 in
Dimension - Outside Diameter inch	0.95 in
Dimension - Strip Length inch	2-7/16

Electrical Ratings

Rating - KVA	35 kV
Rating - Minimum Voltage	600
Voltage - Maximum	35000

Conductor Related

Conductor - Copper DLO Size	313.1 (775/#24) DLO
Conductor - Copper Flex G Size	300 kcmil
Conductor - Copper Flex H Size	300 kcmil
Conductor - Copper Flex I Size	300 kcmil
Conductor - Copper Flex K Size	300 kcmil

Conductor - Copper Flex M Size	300 kcmil
Conductor - Copper Str Size	300 kcmil

Certifications and Compliance

Certification - CSA Approved	Yes
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	UL 486A-486B
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	CM
UL Listed	Yes

Logistics

Minimum Pack Quantity	50
-----------------------	----

For further technical assistance, please contact us

BURNDY Headquarters
47 East Industrial Park Drive
Manchester, New Hampshire 03109

Customer Service Hours:
8 AM - 8 PM Eastern Monday-Friday
Emergency Service 24-hours/365 Days
Phone: 1-800-346-4175
1-603-647-5299 (International)