

YS38LB

by Burndy
Catalog ID: YS38LB

Prop 65 Notice

Copper Compression Belled splice, 700 kcmil, 550 kcmil Class G,H, 550 kcmil, 500-550 kcmil Class I, 500 kcmil Class K,M



Product Details

General

Color Code	Pink
Connector Type	Splice
Die Index	400
Feature - Barrel Style	Belled
Feature - Barrel Type	Standard
Material	Copper
Plated	Y
Plating Type	Tin - Electro Plated
UPC	781810030943
UPC 12 Digit	7818100309433

Dimensions

Dimension - B Length fraction	1-7/8 in
Dimension - B Length inch	1.85 in
Dimension - L Length Overall mm	80 mm
Dimension - Length Overall inch	3.14 in
Dimension - Strip Length inch	1-15/16

Electrical Ratings

Rating - KVA	35 kV
Rating - Minimum Voltage	600
Voltage - Maximum	35000

Conductor Related

Conductor - Copper DLO Size	535.3 (1325/#24)
Conductor - Copper Flex G Size	550
Conductor - Copper Flex H Size	550
Conductor - Copper Flex I Size	500;550
Conductor - Copper Flex K Size	500
Conductor - Copper Flex M Size	500
Conductor - Copper Str Compact Size	700

Conductor - Copper Str Size	700
-----------------------------	-----

Certifications and Compliance

Certification - CSA Approved	Yes
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	UL 486A-486B
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	CM
UL Listed	Yes

Logistics

Minimum Pack Quantity	25
-----------------------	----

For further technical assistance, please contact us

BURNDY Headquarters
47 East Industrial Park Drive
Manchester, New Hampshire 03109

Customer Service Hours:
8 AM - 8 PM Eastern Monday-Friday
Emergency Service 24-hours/365 Days
Phone: 1-800-346-4175
1-603-647-5299 (International)