



Tee, Aluminum Compression

by FARGO
Catalog ID: ORT221212

Tee, Aluminum Compression, Open run Cable to Cable, 0.951-1.045 Main to 0.951-1.045 Tap. TEE, AL COMP 1.03-1.13 IN - 1.03-1.13 IN

* Representative image

Product Details

General

Material	Aluminum
Number of Ground Braid Lug Holes	0
Type	Tee, Aluminum Compression
UPC	096359462880

Dimensions

Base Hole Spacing	0 in
Diameter - Base Holes	0 in
Diameter - Bolt	0 in
Diameter - Inside	0 in
Length - Coupling	0 in
Length Before Compression	0 in
Run Length before Compression	15.7 in
Tap Length before Compression	5.7 in
Weight	2.580 lb

Electrical Ratings

Maximum Current Rating Amps Continuous	0
--	---

Conductor Related

Conductor Compatibility	ACSR-Starling-715.5-26/7;ACSR-Cuckoo-795-24/7;ACSR-Drake-795-26/7;ACSR-Tern-795-45/7;ACSR-Condor-795-54/7;AAC-Cockscomb-900-37;AAC-Snapdragon-900-61;AAC-Magnolia-954-37;AAC-Goldenrod-954-61
Conductor Diameter (Main) - Maximum	1.045 in
Conductor Diameter (Main) - Minimum	0.951 in
Conductor Diameter (Main) Range	0.951 - 1.045

Conductor Diameter (Tap) - Maximum	1.045 in
Conductor Diameter (Tap) - Minimum	0.951 in
Conductor Diameter (Tap) Range	0.951 - 1.045
Conductor Type	• AAC • ACSR

Logistics

Pallet Quantity	60 EA
-----------------	-------

For further technical assistance, please contact us

Domestic Customer Service
Hubbell Power Systems
210 N. Allen Centralia, MO 65240 USA
Phone: (573) 682-5521
Fax: (573) 682-8475
Email: hpscs@hubbell.com

International Customer Service
Phone: +1-573-682-5521
Fax: +1-573-682-8516
Email: hpsintlcs@hubbell.com