



Tee, Aluminum Compression

by ANDERSON
Catalog ID: ORT2108

Tee, Aluminum Compression, Open Run Cable-to-Pad, 0681-0765 Cable, 2-Hole Pad. TEE, AL COMP .682-.765 IN - B2 PAD



* Representative image

Product Details

General

Material	Aluminum
Number of Ground Braid Lug Holes	0
Number of Pad Holes	2
Type	Tee, Aluminum Compression
UPC	096359364504

Dimensions

Base Hole Spacing	0 in
Diameter - Base Holes	0 in
Diameter - Bolt	0 in
Diameter - Inside	0 in
Length - Coupling	0 in
Length Before Compression	0 in
Run Length before Compression	12.7 in
Weight	1.176 lb
Width - Flat Bar Tap	2 in

Electrical Ratings

Maximum Current Rating Amps Continuous	0
--	---

Conductor Related

Conductor Compatibility	ACSR-Merlin-336.4-18/1;ACSR-Linnet-336.4-26/7;ACSR-Oriole-336.4-30/7;ACSR-Chickadee-397.5-18/1;ACSR-Brahma-203.2-16/19;AAC-Canna-397.5-19
Conductor Diameter (Main) - Maximum	0.765 in
Conductor Diameter (Main) - Minimum	0.681 in

Conductor Diameter (Main) Range	0.681 - 0.765
Conductor Type	• AAC • ACSR

For further technical assistance, please contact us

Domestic Customer Service

Hubbell Power Systems
210 N. Allen Centralia, MO 65240 USA
Phone: (573) 682-5521
Fax: (573) 682-8475
Email: hpscs@hubbell.com

International Customer Service

Phone: +1-573-682-5521
Fax: +1-573-682-8516
Email: hpsintlcs@hubbell.com