



Tee, Aluminum Compression

by ANDERSON
Catalog ID: ORT2113

Tee, Aluminum Compression, Open Run Cable-to-Pad, 1141-1235 Cable, 2-Hole Pad. TEE, AL COMP 1.14-1.235 IN - C PAD



* Representative image

Product Details

General

Material	Aluminum
Number of Ground Braid Lug Holes	0
Number of Pad Holes	4
Type	Tee, Aluminum Compression
UPC	096359366195

Dimensions

Base Hole Spacing	0 in
Diameter - Base Holes	0 in
Diameter - Bolt	0 in
Diameter - Inside	0 in
Length - Coupling	0 in
Length Before Compression	0 in
Run Length before Compression	19.5 in
Weight	4.136 lb
Width - Flat Bar Tap	3 in

Electrical Ratings

Maximum Current Rating Amps Continuous	0
--	---

Conductor Related

Conductor Compatibility	ACSR-Canary-900-54/7;ACSR-Rail-954-45/7;ACSR-Cardinal-954-54/7;ACSR-Ortolan-1033.5-45/7;AAC-Camellia-1000-61;AAC-Bluebell-1033.5-37;AAC-Larkspur-1033.5-61;AAC-Marigold-1113-61
Conductor Diameter (Main) - Maximum	1.235 in
Conductor Diameter (Main) - Minimum	1.141 in

Conductor Diameter (Main) Range	1.141 - 1.235
Conductor Type	• AAC • ACSR

Logistics

Pallet Quantity	180 EA
-----------------	--------

For further technical assistance, please contact us

Domestic Customer Service

Hubbell Power Systems
210 N. Allen Centralia, MO 65240 USA
Phone: (573) 682-5521
Fax: (573) 682-8475
Email: hpscscs@hubbell.com

International Customer Service

Phone: +1-573-682-5521
Fax: +1-573-682-8516
Email: hpsintlcs@hubbell.com