


RIGID REDUCING BUSHINGS - STEEL

Reducing Bushings Steel

B34





Catalog #: 1145

APPLICATIONS

For use with threaded rigid/IMC conduit to reduce the size of a female hub to accommodate a smaller size of conduit or male threaded hub Rugged steel construction insures mechanical protection of the raceway

PRODUCT FEATURES

Zinc electro plated for corrosion protection

N/A

CULUS

UL Listed E195969

GENERAL PRODUCT INFORMATION

Trade Size: 1-1/4 in. to 1/2 in.

DRAWING DIMENSIONS

Dimension A: 1-5/8 in.

1-5/8 in. 1-1/4 in. - 11-1/2 NPS 39/64 in. 1/2 in. - 14 NPS 11/16 in. Thread Spec. A: Dimension B: Thread Spec. B: Dimension C:

PACKAGING

CKAGING
Package Type:
Ship Carton Qty.:
Product UPC-A Labeled:
Weight (Lbs. Per/C):
Ship Carton Length (in.):
Ship Carton Width (in.):
Ship Carton Height (in.):
Cth Weight (lbs.): Carton 50 No 26.80 8.25 5.00 4.00 Ctn Weight (Lbs.): UPC Number: 13.40 050169011454 12of5: 50050169011459

Page 1 / 1