


## Heavy duty grade receptacles

### Product description


2-pole, 3-wire grounding  
15A, 125V/AC  
20A, 125V/AC



5-15R

5-20R

### Design features

- Heavy duty grade receptacles are designed and built for heavier use and feature enhanced ground contacts
- Tamper resistant receptacles provide compliance with 2014 NEC® Article 406.12 which states that all 15A and 20A, 125V/AC receptacles installed in dwelling units must be tamper resistant 
- Durable impact-resistant thermoplastic face and back body is virtually unbreakable and also chemical-resistant
- Side-wire terminals accept up to #10 AWG solid wire
- Screw-catch feature on duplex devices speeds mounting of wallplates
- Galvanized steel wrap-around mounting strap for superior assembly security
- Patented built-in wire stripper for #12 and #10 AWG wire (except TRCR models) to speed installation
- Duplex and decorator devices feature automatic grounding system that eliminates the need for bonding jumper in grounded metal enclosures and provides a redundant measure of ground continuity where a jumper is used



TRCR15



TR6250



1877

### Heavy duty tamper resistant duplex receptacles



Rating A	V/AC	Description	Color suffix	Catalog no.	
15	120	Tamper resistant NEMA 5-15R duplex receptacle, side wire	A, B, BK, GY, LA, RD, V, W	□ TRCR15__	•
20	125	Tamper resistant NEMA 5-20R duplex receptacle, side wire	A, B, BK, GY, LA, RD, V, W	□ TRCR20__	•

cULus Listed to UL498, file no. E15058; NOM certified

### Heavy duty tamper resistant single receptacles



Rating A	V/AC	Description	Color suffix	Catalog no.	
15	125	Tamper resistant NEMA 5-15R decorator single receptacle, side wire	B, BK, V, W	□ TR6250__	•
		Tamper resistant NEMA 5-15R single receptacle, side wire	A, B, BK, LA, V, W	□ TR817__	•
20	125	Tamper resistant NEMA 5-20R decorator single receptacle, side wire	LA, V, W	□ TR6350__	•
		Tamper resistant NEMA 5-20R single receptacle, side wire	A, B, BK, LA, V, W	□ TR1877__	•

cULus Listed to UL498, file no. E15058; NOM certified

### Heavy duty single receptacles



Rating A	V/AC	Description	Color suffix	Catalog no.	
15	125	5-15R Single receptacle, side wire	B, BK, LA, V, W	□ 817__	• •
20	125	5-20R Single receptacle, side wire	A, B, BK, LA, V, W	□ 1877__	• •

Listed to UL498, file no. E15058; CSA certified to C22.2, no. 42; NOM certified

### Color ordering information:

For ordering devices, include Catalog no. followed by the Color suffix: A (Almond), B (Brown), BK (Black), GY (Gray), LA (Light Almond), RD (Red), V (Ivory), W (White)

A	B	BK	GY	LA	RD	V	W
(Almond)	(Brown)	(Black)	(Gray)	(Lt. Almond)	(Red)	(Ivory)	(White)

**Dimensional information:** B-68, B-69 **Specification information:** Please visit [www.eaton.com/wiringdevices](http://www.eaton.com/wiringdevices)  
**Compliances, specifications and availability are subject to change without notice.**

 Indicates NAFTA compliant - Page G-21

 RoHS compliant - Page G-21

 Tamper resistant

## Straight blade receptacle families

### High performance receptacles for the most demanding of environments

Arrow Hart's offering of straight blade receptacles cover the full range of hospital, industrial, construction and commercial grades along with special solutions like corrosion resistant, severe duty insulated and watertight straight blade receptacles for complex environments



#### Hospital grade straight blade receptacles

Arrow Hart's feature rich line of hospital grade receptacles have been designed to meet and exceed the demanding requirements of UL498 and federal specification WC-596 to provide a consistent means of connectivity where downtime can be critical.



#### Industrial grade straight blade receptacles

Designed from the inside out, these receptacles meet and exceed the UL498 and federal specification WC-596 standards to withstand the most abusive environments and excel in applications that demand the highest levels of performance.



#### Commercial & construction grade straight blade receptacles

Engineered for safe, reliable performance, these UL498 and federal specification WC-596 listed devices provide maximum durability in a wide variety of applications while providing installation efficiency to help finish the job on time.



#### Industrial grade corrosion resistant straight blade receptacles

Built to defy the potentially damaging effects of moisture, humidity and other corrosive elements, Arrow Hart corrosion resistant devices are listed to UL498 and federal specification WC-596 to provide a dependable connection regardless of the application environment.





#### Industrial grade watertight straight blade receptacles

Listed to UL498, Arrow Hart watertight straight blade receptacles utilize advanced materials and innovative design features to make them the best choice for superior performance in harsh, wet location environments.


### Commercial grade straight blade receptacles

#### Product description


2-pole, 3-wire grounding  
15A, 125V/AC  
20A, 125V/AC  
NEMA 5-15R, 5-20R




BR20



CR20



1877



6352

#### Commercial grade receptacles



Rating	A	V/AC	NEMA	Description	Color suffix	Catalog no.			
15	125	5-15R	Duplex receptacle, back & side wire	A, B, BK, GY, LA, V, W	□ BR15__				
			Duplex receptacle, side wire	A, B, BK, GY, LA, V, W	□ CR15__				
			Single receptacle, side wire	B, BK, LA, V, W	□ 817__*				
20	125	5-20R	Duplex receptacle, back & side wire	A, B, BK, GY, LA, RD, V, W	□ BR20__				
			Duplex receptacle, side wire	A, B, BK, GY, LA, V, W	□ CR20__				
			Single receptacle, side wire	A, B, BK, LA, V, W	□ 1877__*				

\* Not Fed Spec

#### Decorator commercial grade receptacles



Rating	A	V/AC	NEMA	Description	Color suffix	Catalog no.			
15	125	5-15R	Duplex receptacle, back & side wire	B, BK, GY, LA, V, W	□ 6252__†				
			Single receptacle, back & side wire	V, W	□ 6250__*				
20	125	5-20R	Duplex receptacle, back & side wire	A, B, BK, GY, LA, V, W	□ 6352__†				
			Single receptacle, back & side wire	B, V, W	□ 6350__*†				

† Not NOM cert, \* UL Listed & CSA certified

#### Accessories for construction grade 5-15 & 5-20 receptacles

Description	Color suffix	Catalog no.		
2-Gang standard size duplex receptacle wallplate	A, B, BK, GY, LA, RD, V, W	□ 5150__		
1-Gang mid-size single receptacle wallplate, 1.4" hole	A, B, BK, GY, LA, RD, V, W	□ PJ7__		



5150B



PJ7GY

#### Color ordering information:

For ordering devices, include Catalog no. followed by the Color suffix: A (Almond), B (Brown), BK (Black), GY (Gray), LA (Light Almond), RD (Red), V (Ivory), W (White)

A	B	BK	GY	LA	RD	V	W
(Almond)	(Brown)	(Black)	(Gray)	(Lt. Almond)	(Red)	(Ivory)	(White)

**Specification information:** Commercial receptacles: A-33

**Compliances, specifications and availability are subject to change without notice.**

Build-to-spec customizable devices - Page A-6

Indicates NAFTA compliant - Page Q-32

RoHS compliant - Page Q-32