

# 1.5

## Loadcenters and Circuit Breakers

### Classified Circuit Breakers

1

**Type CL Replacement Breakers for Square D HOMELINE, General Electric, Crouse-Hinds, Thomas & Betts, Murray and ITE®/Siemens Loadcenters**

CL\_

#### Type CL Breakers, 1-Inch (25.4 mm) per Pole, 10 kAIC



| Ampere Rating | Wire Size Range Cu/Al<br>60 °C or 75 °C | Single-Pole 120/240 V<br>Requires One<br>1-Inch (25.4 mm) Space<br>10 per Shelf Carton<br>Catalog Number | Two-Pole 120/240 V<br>Common Trip Requires Two<br>1-Inch (25.4 mm) Spaces<br>5 per Shelf Carton<br>Catalog Number |
|---------------|-----------------------------------------|----------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------|
|               |                                         |                                                                                                          |                                                                                                                   |
| 15            | #14-4                                   | CL115                                                                                                    | CL215                                                                                                             |
| 20            | #14-4                                   | CL120                                                                                                    | CL220                                                                                                             |
| 25            | #14-4                                   | CL125                                                                                                    | CL225                                                                                                             |
| 30            | #14-4                                   | CL130                                                                                                    | CL230                                                                                                             |
| 35            | #14-4                                   | CL135                                                                                                    | CL235                                                                                                             |
| 40            | #14-4                                   | CL140                                                                                                    | CL240                                                                                                             |
| 45            | #14-4                                   | CL145                                                                                                    | CL245                                                                                                             |
| 50            | #14-4                                   | CL150                                                                                                    | CL250                                                                                                             |

CL\_AF

#### Type CL Classified Arc and Ground Fault Breakers (5 Milliampere), 1-Inch (25.4 mm) per Pole, 10 kAIC





Single-Pole 120/240 V  
Requires One 1-Inch (25.4 mm) Space  
1 per Shelf Carton  
Catalog Number

| Ampere Rating         | Wire Size Range Cu/Al<br>60 °C or 75 °C |          |
|-----------------------|-----------------------------------------|----------|
| Arc Fault Breakers    |                                         |          |
| 15                    | #14-4                                   | CL115AF  |
| 15                    | #14-4                                   | CL115CAF |
| 20                    | #14-4                                   | CL120AF  |
| 20                    | #14-4                                   | CL120CAF |
| Ground Fault Breakers |                                         |          |
| 15                    | #14-4                                   | CL115GFT |
| 20                    | #14-4                                   | CL120GFT |
| 30                    | #14-4                                   | CL130GFT |

CLR\_

#### Type CL Classified Latching Remote Control Smart Breakers™, 1-Inch (25.4 mm) per Pole, 10 kAIC



| Ampere Rating | Wire Size Range Cu/Al<br>60 °C or 75 °C | Single-Pole 120 V<br>Requires One<br>1-Inch (25.4 mm) Space<br>10 per Shelf Carton<br>Catalog Number | Two-Pole 120/240 V<br>Common Trip Requires Two<br>1-Inch (25.4 mm) Spaces<br>5 per Shelf Carton<br>Catalog Number |
|---------------|-----------------------------------------|------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------|
|               |                                         |                                                                                                      |                                                                                                                   |
| 15            | (2) #14-10                              | CLRP115                                                                                              | CLRP215                                                                                                           |
| 20            | (2) #14-10                              | CLRP120                                                                                              | CLRP220                                                                                                           |
| 25            | (1) #8-6                                | CLRP125                                                                                              | CLRP225                                                                                                           |
| 30            | (1) #8-6                                | CLRP130                                                                                              | CLRP230                                                                                                           |