Product data sheet Characteristics

XVR12B05S

Harmony XVR, Rotating beacon, Ø120, orange, with buzzer 50...90 dB, 24 V AC/DC

Product availability: Non-Stock - Not normally stocked in distribution facility



Price*: 216.00 USD



Main

		<u> </u>
Range of product	Harmony XVR	
Product or component type	Prewired rotating mirror beacon	
Sound signalling	Buzzer	
Device short name	XVR	ab.
Mounting diameter	4.72 in (120 mm)	
IP degree of protection	IP23 IEC 60529	
[Us] rated supply voltage	24 V AC/DC	ering Ering
Light source	High luminosity LED, orange	idi
Noise level	5090 dB continuous or intermittent tone)1 m	

Complementary

Material	ABS (acrylonitrile butadiene-styrene) body part AS globe	
CAD overall width	4.72 in (120 mm)	
CAD overall depth	4.72 in (120 mm)	
Net Weight	1.10 lb(US) (0.5 kg)	
Marking	CE	
Product mounting	By 3 M5 screws	
Supply voltage limits	1930 V DC 21.626.4 V AC	
[Uimp] rated impulse withstand voltage	0.8 kV	
Current consumption	196 mA	
Flashing frequency	2.3 Hz	
Clamping connection capacity	0.83 mm²	
AWG gauge	AWG 18	

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Cable length	15.75 in (400 mm)	

Environment

Standards	EN 61000-6-4 EN 61000-6-2
Protective treatment	TC
Ambient air temperature for storage	-31158 °F (-3570 °C)
Ambient air temperature for operation	14122 °F (-1050 °C)
Electrical shock protection class	Class II IEC 61140

Ordering and shipping details

<u> </u>	
Category	22617 - XVC TOWER LIGHTS
Discount Schedule	XV
GTIN	03606480033247
Nbr. of units in pkg.	1
Package weight(Lbs)	22.50 oz (638 g)
Returnability	No
Country of origin	JP

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	7.68 in (19.5 cm)	
Package 1 width	5.51 in (14 cm)	
Package 1 Length	5.51 in (14 cm)	

Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End of Life Information	

Contractual warranty


Warranty	18 months	


Product data sheet Dimensions Drawings

XVR12B05S

Rotating Mirror Beacon

Dimensions





Product data sheet Mounting and Clearance

XVR12B05S

Rotating Mirror Beacon

Panel Cut-out

