


OY043S



Safety light curtain

OYA0460-30-4-12-P-1

For 8-wire cordsets the core colors are not standardized.
Please note the wiring of the sensor and the cordsets (see data sheet).



- T transmitter
- R receiver
- 1 LED three-color red / green / orange
- 2 LED yellow
- 3 LED 2-color red/green



Product characteristics

Type of light	Infrared light
Dimensions [mm]	513 x 28 x 30

Application

Protective function	Access prevention hand protection
---------------------	-----------------------------------



Safety light curtain

OYA0460-30-4-12-P-1

Electrical data		
Operating voltage tolerance	[%]	20
Operating voltage	[V]	24 DC
Protection class		III
Reverse polarity protection		yes
Power-on delay time	[s]	< 2
Type of light		Infrared light
Wave length	[nm]	950
Receiver		
Current consumption	[mA]	83
Transmitter		
Current consumption	[mA]	42
Outputs		
Electrical design		PNP
Number of OSSD outputs		2
Max. current load per OSSD output	[mA]	400; (24 V)
Short-circuit protection		yes
Monitoring range		
Protected area height	[mm]	460
Resolution (detection capacity d)	[mm]	30
Protection area width (low light intensity)	[m]	0...4
Protection area width (high light intensity)	[m]	3...12
Reaction times		
Response time	[ms]	7.5
Operating conditions		
Applications		Class C to EN 60654-1 weatherproof application
Ambient temperature	[°C]	-10...55
Storage temperature	[°C]	-20...70
Max. relative air humidity	[%]	95
Protection		IP 65; IP 67
Tests / approvals		
EMC		IEC 61496-1
Shock resistance		IEC 61496-1
Vibration resistance		IEC 61496-1

OY043S



Safety light curtain

OYA0460-30-4-12-P-1

Safety classification

ESPE type (IEC 61496-1)	4
ISO 13849-1	Category 4, PL e
IEC 61508	SIL 3
IEC 62061	SIL cl 3
Mission time TM [h]	175200
Safety-related reliability PFHD [1/h]	9.5E-09

Mechanical data

Weight [g]	2000
Dimensions [mm]	513 x 28 x 30
Material	housing: aluminum; front lens: PC
Length L [mm]	513

Displays / operating elements

Display	transmitter	1 x LED
	receiver	2 x LED

Accessories


Items supplied	Assembly angle: 4
	Slot nuts: 4
	Nuts

Remarks

Pack quantity	1 pcs.
---------------	--------

Electrical connection - receiver

Connector: 1 x M12; Maximum cable length: 100 m; for wire cross-section 0.34 mm²




OY043S



Safety light curtain


OYA0460-30-4-12-P-1

Connection



Electrical connection - transmitter

Connector: 1 x M12



OY043S



Safety light curtain

OYA0460-30-4-12-P-1

Connection

