


E12553



Y connection cable

YDOGS040PLS0002H02



Application

System	Free from silicone; Halogen-free; Drag chain suitability
Free from silicone	yes

Electrical data

Operating voltage [V]	8...32 DC
Protection class	III
Max. current load total [A]	4

Operating conditions

Ambient temperature [°C]	-40...85
Ambient temperature (moving) [°C]	-20...85
Protection	IP 67; (mating connector plugged in)

Mechanical data

Weight	[g]	154.2	
Dimensions	[mm]	24 x 24 x 54	
Material		PA	
Number of ports splitter box		2	
Drag chain suitability		yes	
Drag chain suitability		Bending radius for flexible applications	min. 10 x cable diameter
		Travel speed	max. 3.3 m/s for a horizontal travel length of 5 m and max. acceleration of 5 m/s²
		Bending cycles	> 5 Mio.
		Torsional strain	± 180 °/m

E12553



Y connection cable

YDOGS040PLS0002H02

Remarks


Pack quantity	2 pcs.
---------------	--------

Electrical connection


Cable: 2 m, PUR, Halogen-free, black, Ø 5.4 mm; 2 x 0.50 mm² (28 x Ø 0.15 mm)

Electrical connection - Socket

Connector: 1 x DEUTSCH connector; Contacts: nickel-plated



Connection



Core colors :
BK = black
BN = brown