

1) Teach-in reference image, 2) Operating voltage, 3) Output 1 active, 4) Output 2 active, 5) Connection with PC, 6) Focus



Basic features

Application	Multi-Code-Reading Verifying character strings
Approval/Conformity	CE cULus EAC WEEE
Style	Square Connection 90°

Display/Operation

Adjuster	Adjusting ring button
Setting	Image sharpness Teach-in reference image

Electrical connection

Connection 1	M12x1-Male, 8-pin, A-coded
Connection 2	M12x1-Male, 4-pin, D-coded
Contact, surface protection	Gold plated
Polarity reversal protected	yes
Short-circuit protection	yes

Electrical data

Input function	Trigger
No-load current I_o max. at U_e	200 mA
Operating voltage U_b	22...26 VDC
Rated operating current I_e	100 mA
Rated operating voltage U_e DC	24 V
Ready delay t_v max.	10 ms
Ripple max. (% of U_e)	10 %
Voltage drop U_d max. at I_e	1.8 V

Environmental conditions

Ambient temperature	-10...55 °C
EN 60068-2-27, Shock	Half-sinus, 100 gn, 2 ms, 3x8000 Half-sinus, 30 gn, 11 ms, 3x6
EN 60068-2-6, Vibration	10...2000 Hz, amplitude 1 mm, 30 gn, 3x5 h 55 Hz, amplitude 1 mm, 3x30 min
IP rating	IP54

Functional Characteristics

2D codes	Data Matrix ECC 200 QR code Mini QR
Barcodes	Interleaved 2-of-5, Code 39, Code 128, Pharmacode, Codabar, EAN 8, EAN 13, UPC-E, UPC-A
Features per inspection, number max.	255
Inspections, number max.	20
Stacked codes	PDF417

Functional safety

MTTF (40 °C)	127 a
---------------------	-------

Material

Housing material	Aluminum, Die casting, Painted ABS
Material sensing surface	PMMA
Surface protection	Painted

Mechanical data

Dimension	51.5 x 70 x 40 mm
Mounting part	Screw M4

Remarks

Do not press key using a pointed tool.
For additional information, refer to user's guide.
Order accessories separately.
Detection rate is dependent on the evaluation function.
Interface plug, if n.c. protect against ingress of dust, dirt and liquids. Cover cap included.
Only for applications per NFPA 79 (machines with a supply voltage of maximum 600 V). Appropriate connectors can be obtained from Balluff.
Use of external illumination recommended for working distances greater than 300 mm .
Do not use sensor where object is exposed to strong ambient light.
For more information about MTTF and B10d see MTTF / B10d Certificate

Indication of the MTTF- / B10d value does not represent a binding composition and/or life expectancy assurance; these are simply experiential values with no warranty implications. These declared values also do not extend the expiration period for defect claims or affect it in any way.

Optical features

Field of view max.	240 x 180 mm
Field of view min.	43 x 32 mm
Focal length	16.0 mm
Frame rate	3...15 Hz
Image resolution	640 x 480 pixels
LED group per IEC 62471	Exempt Group
Light type	LED, red light
Sensor type Vision	CMOS image sensor black-white
Special optical feature	Incident light, can be disabled
Wave length	630 nm


Output/Interface

Duration of time function	Impulse 1...1000 ms or infinite
Interface	Ethernet 10/100 Base T RS232 (9.6...115.2 kBaud)
Supplementary output	Trigger output PNP
Switching output	3x PNP normally open (NO)
Time function	On/off delay Single pulse

Range/Distance


Operating Distance	150...1000 mm
---------------------------	---------------

Connector Drawings



Wiring Diagrams

Conn. "PWR IO"



Conn. "To PC"

