








7/8" JIN Junction Blocks

4 Port, 4 Pin/3 Wire JIN Junction blocks



Standard Wiring | MIN Receptacle & Cable | IP67 Protection Rating

Trunk Style	Trunk Connection	Part Number	Circuit
	MIN Size I 6 Pole Male Receptacle	JIN-440-006-M000	
	Yellow PVC ST00W 6 x 16 AWG 600V 13.3mm OD	JIN-440-006-C**	

Cables for JIN-440-006-M000				Female Receptacle	
Single Ended Home Run Cable		Double Ended Home Run Cable			
MIN-6FP-*	Page A-25	MIN-6MFP-*	Page A-31	MIN-6FR-1	Page A-46

* Length in feet. Standard Cable lengths are 3, 6, 12, 20, 30 & 50 feet. Consult factory for other lengths.

** Lengths in meters. Standard Cable lengths are 2, 5 & 10 meters. Consult factory for other lengths.

Standard housing is aluminum alloy, for stainless steel housing add a "SS" right after JIN. (e.g. JIN-440-006-M000 becomes JINSS-430-006-M000)

Specifications:

Housing:	Black Epoxy Coated Die Cast Aluminum Alloy
Connectors:	Anodized Aluminum, Oil Resistant PVC Contact Carrier
Cable Gland:	Nickel Plated Brass, Polyamide and TPE Inserts
Contacts:	Copper Alloy with Gold Plating
Temperature:	-30°C to +80°C (-22°F to +176°F)
Amperage:	4A per Port, 8A per Unit