



Ethernet (M12) Series Etherplug Cordsets

4 Conductor Ethernet Series Cordsets, 24AWG



Double Ended Cordsets | 300V, 4A | CAT5e | D-Coded | Twisted Pairs | IP67 Rating




Only Male to Female versions are UL listed for safety concerns




Ethernet Series

L



M12 x 1

Male Faceview	Cables	Features	Male to Female 	Male to Male	Female to Female
	Teal PVC AWM 4 X 24 AWG 300V, 4A -20°C to +80°C 6.1mm OD	Industry Standard PVC	MDE45-4MFP-**	MDE45-4MMP-**	MDE45-4FFP-**
	Teal PVC AWM With Foil & Braided Shield 4 X 24 AWG 300V, 4A -20°C to +80°C 6.1mm OD	Industry Standard PVC Foil & Braided Shield	MDE45B-4MFP-**	MDE45B-4MMP-**	MDE45B-4FFP-**
	Teal PUR AWM 4 X 24 AWG 300V, 4A -40°C to +80°C 5.6mm OD	Continuous-Flex Oil and Cutting Fluid Resistant Cut Resistant PUR	MDE45P-4MFP-**	MDE45P-4MMP-**	MDE45P-4FFP-**
	Teal PUR AWM With Foil & Braided Shield 4 X 24 AWG 300V, 4A -40°C to +80°C 6.4mm OD	Continuous-Flex Oil and Cutting Fluid Resistant Cut Resistant PUR Foil & Braided Shield	MDE45PB-4MFP-**	MDE45PB-4MMP-**	MDE45PB-4FFP-**
	Teal PUR AWM With Foil & Braided Shield 4 X 24 AWG 300V, 4A -40°C to +80°C 6.4mm OD	Continuous-Flex Oil and Cutting Fluid Resistant Cut Resistant PUR Foil & Braided Shield to Coupling Nut	MDE45PB-4MFPS-**	MDE45PB-4MMPS-**	MDE45PB-4FFPS-**
	TPE AWM With Foil & Braided Shield 4 X 24 AWG 300V, 4A -40°C to +80°C 6.6mm OD	Continuous-Flex Weld Slag Resistant TPE Foil & Braided Shield	MDE45WB-4MFP-** (Teal) MDE45WB-4MFP-**-RD (Red)	MDE45WB-4MMP-** (Teal) MDE45WB-4MMP-**-RD (Red)	MDE45WB-4FFP-** (Teal) MDE45WB-4FFP-**-RD (Red)
	TPE AWM With Foil & Braided Shield 4 X 24 AWG 300V, 4A -40°C to +80°C 6.6mm OD	Continuous-Flex Weld Slag Resistant TPE Foil & Braided Shield to Coupling Nut	MDE45WB-4MFPS-** (Teal) MDE45WB-4MFPS-**-RD (Red)	MDE45WB-4MMPS-** (Teal) MDE45WB-4MMPS-**-RD (Red)	MDE45WB-4FFPS-** (Teal) MDE45WB-4FFPS-**-RD (Red)

** Lengths in meters. Standard cable lengths are 1, 2, 4, 5, 6, 10 & 15 meters. Consult factory for other lengths.

Standard coupling nut is nickel plated brass, for stainless steel coupling nut add a "SS" suffix. (e.g. MDE45-4MFP-1M becomes MDE45-4MFP-1M-SS)



Male Plug



Female Plug