

Signal tower / Pre-assembled Signal Tower

SignalSET Stand



Part No.: 649.191.05 Series: KombiSIGN 72

| MECHANICAL DATA | |
|-----------------------------|-----------------|
| Height | 1510 mm |
| Materials | Stainless steel |
| Cable entry | Through hole |
| Tension relief | Not present |
| Type of fixing | Tube mounting |
| Working temperature minimum | -20°C |
| Working temperature maximum | +50°C |
| Weight with packaging | 8900 g |
| Product weight | 7100 g |

| APPROVAL DATA | |
|-------------------------------|-----|
| Conforms with CE | No |
| WEEE | Yes |
| Conforms with RED directive | No |
| Conform with ATEX-directive | No |
| Conforms with CCC-Ex | No |
| Conforms with CCC | No |
| Conforms with UL | No |
| Conforms with FCC | No |
| Conforms with IC | No |
| EAC certificate available | No |
| Conforms with UKCA (Importer) | No |
| Conforms with CMIM | No |
| Conforms with AS-I | No |
| Conforms with GL | No |
| Conforms with RoHS CN | No |
| Conforms with VdS | No |

For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.