



PS316-T12-K360

- thermoplastic enclosure with foldable latching cover
- Quick connection technology as connection terminals rotated by 45°
- Simple and quick to adjust the control elements by 45°.
- cable entry 1 x M20 x 1,5
- Design to EN 50041

Data

Ordering data

EAN (European Article Number) 4030661502694

Approval - Standards

Certificates cULus

CCC EAC

General data

Standards IEC 60947-5-1

Housing construction form Norm construction design

Enclosure material Plastic, glass-fibre-reinforced

Material of the contacts, electrical Silver

Gross weight 119.3 g

General data - Features

Safety functions Yes

Number of auxiliary contacts 1

Number of safety contacts 2

Safety appraisal

Standards EN ISO 13849-1

Mission Time 20 Year(s)

Safety appraisal - Safety outputs

B10d Normally-closed contact (NC) 20,000,000 Operations

Mechanical data

Actuating element Offset roller lever K360

Mechanical life, minimum 10,000,000 Operations

Positive break force, minimum 50 N

Actuating speed, minimum 60 mm/min

Actuating speed, maximum 1 m/s

Mechanical data - Connection technique

Terminal Connector Screw connection

Cable section, minimum 0.34 mm²

Cable section, maximum 1.5 mm²

Mechanical data - Dimensions

Length of sensor 37 mm

Width of sensor 41 mm

Height of sensor 129 mm

Ambient conditions

Degree of protection IP66

IP67

Ambient temperature, minimum -30 °C

Ambient temperature, maximum +80 °C

Ambient conditions - Insulation value

Rated insulation voltage U_i 300 V

Rated impulse withstand voltage U_{imp} 4 kV

Electrical data

Thermal test current 5 A

Required rated short-circuit current to EN 60947-5-1 400 A

Utilisation category AC-15 240 VAC

Utilisation category AC-15 3 A

Utilisation category DC-13 24 VDC

Utilisation category DC-13 3 A

Switching element 1 NO contact, 2 NC contacts

Switching principle Creep circuit element

Switching frequency 5,000 /h

Schmersal, Inc., 15 Skyline Drive, Hawthorne, NY 10532

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 11/9/2021, 11:40 AM