



## PS216-Z11-J200

- **only for positioning tasks**
- Lever angle adjustable in 15° steps
- Simple and quick to adjust the control elements by 45°.
- thermoplastic enclosure with foldable latching cover
- Quick connection technology as connection terminals rotated by 45°
- cable entry 1 x M20 x 1,5
- Design to EN 50047

## Data

### Ordering data

EAN (European Article Number) 4030661502243

### Approval - Standards

Certificates cULus  
CCC  
EAC

### General data

|                                      |                                 |
|--------------------------------------|---------------------------------|
| Standards                            | IEC 60947-5-1                   |
| Housing construction form            | Norm construction design        |
| Enclosure material                   | Plastic, glass-fibre-reinforced |
| Material of the contacts, electrical | Silver                          |
| Gross weight                         | 190 g                           |

## General data - Features

Number of auxiliary contacts 1

Number of safety contacts 1

## Safety appraisal

Standards EN ISO 13849-1

Mission Time 20 Year(s)

## Safety appraisal - Safety outputs

B10d Normally-closed contact (NC) 20,000,000 Operations

## Mechanical data

Actuating element Rod lever J200

Mechanical life, minimum 10,000,000 Operations

Positive break force, minimum 40 N

Actuating speed, minimum 10 mm/min

Actuating speed, maximum 1 m/s

## Mechanical data - Connection technique

Terminal Connector Screw connection

Cable section, minimum 0.34 mm<sup>2</sup>

Cable section, maximum 1.5 mm<sup>2</sup>

## Mechanical data - Dimensions

Length of sensor 32.5 mm

Width of sensor 31 mm

Height of sensor 180.5 mm

## Ambient conditions

|                              |              |
|------------------------------|--------------|
| Degree of protection         | IP66<br>IP67 |
| Ambient temperature, minimum | -30 °C       |
| Ambient temperature, maximum | +80 °C       |

## Ambient conditions - Insulation value

|                                           |       |
|-------------------------------------------|-------|
| Rated insulation voltage $U_i$            | 300 V |
| Rated impulse withstand voltage $U_{imp}$ | 4 kV  |

## Electrical data

|                                                      |                             |
|------------------------------------------------------|-----------------------------|
| Thermal test current                                 | 10 A                        |
| Required rated short-circuit current to EN 60947-5-1 | 400 A                       |
| Utilisation category AC-15                           | 240 VAC                     |
| Utilisation category AC-15                           | 3 A                         |
| Utilisation category DC-13                           | 24 VDC                      |
| Utilisation category DC-13                           | 3 A                         |
| Switching element                                    | 1 NO contact, 1 NC contacts |
| Switching principle                                  | Snap switch element         |
| Switching frequency                                  | 5,000 /h                    |

Schmersal, Inc., 15 Skyline Drive, Hawthorne, NY 10532

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 11/9/2021, 11:11 AM