



## EDRRS40RT

- Metal actuators
- Key unlatching
- Projection from front of panel 35 mm

## Data

### Ordering data

|                               |               |
|-------------------------------|---------------|
| EAN (European Article Number) | 4030661448503 |
| eCl@ss number, Version 9.0    | 27-37-12-12   |
| eCl@ss number, Version 11.0   | 27-37-12-12   |
| ETIM number, version 6.0      | EC001038      |

### Approval - Standards

|              |              |
|--------------|--------------|
| Certificates | cULus<br>CCC |
|--------------|--------------|

### General data

|                                 |  |
|---------------------------------|--|
| Standards                       | IEC/EN 60947-5-5<br>EN ISO 13850:2006    |
| Versions                        | Embeddable button - Front plate mounting |
| Design                          | Round                                    |
| Material of the operators       | Brass, coated                            |
| Colour of the operating element | Red                                      |

|              |      |
|--------------|------|
| Gross weight | 60 g |
|--------------|------|

## General data - Features

|                  |     |
|------------------|-----|
| Safety functions | Yes |
| Latching         | Yes |

## Mechanical data

|                                |                    |
|--------------------------------|--------------------|
| Unlocking                      | Key unlatching     |
| Mechanical life, minimum       | 100,000 Operations |
| Actuating stroke               | 5 mm               |
| Mounting                       | mounting flange    |
| Tightening torque of the screw | 0.6 Nm             |

## Mechanical data - Dimensions

|  |               |
|--|---------------|
| Height                                   | 35 mm         |
| Diameter of cap                          | 37.5 mm       |
| Diameter hole                            | 22.3 mm       |
| Diameter hole, with tolerance indication | 22.3 + 0.4 mm |
| Thickness, of the front panel, minimum   | 1.5 mm        |
| Thickness of the front panel, maximum    | 6 mm          |

## Ambient conditions

|                              |             |
|------------------------------|-------------|
| Degree of protection         | IP65        |
| Ambient temperature, minimum | -25 °C      |
| Ambient temperature, maximum | +75 °C      |
| Resistance to shock          | 70 g / 4 ms |

## Electrical data

Switching frequency

600 /h

Schmersal, Inc., 15 Skyline Drive, Hawthorne, NY 10532

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 11/9/2021, 8:55 AM