



SET SL 300-0450

- Robust design
- 2 Contacts
- Can be mounted on existing glue-spreading machines, veneering presses, etc.
- Various lengths available

Data

Ordering data

eCl@ss number, Version 9.0 27-27-06-90

eCl@ss number, Version 11.0 27-27-06-90

Note (Ordering data) Note: The position switch with safety function is not included in delivery. The following variants can be selected: 1 NO/1 NC T3K 335-11Z-U90 - metal enclosure
T3K 336-11Z-U90 - thermoplastic enclosure

General data

Standards	EN 60947-5-1
Material of the latching	Glass-fibre, thermoplastic
Material of the profile strip	Aluminium
Side plate material	Aluminium
Gross weight	2,910 g

Mechanical data - Dimensions

Width	100 mm
Height	260 mm

Length (L1)	450 mm
-------------	--------

Ambient conditions

Degree of protection	IP67 to EN 60529
----------------------	------------------

Ambient temperature, minimum	-20 °C
---------------------------------	--------

Ambient temperature, maximum	+55 °C
---------------------------------	--------

Storage and transport temperature, minimum	-20 °C
---	--------

Storage and transport temperature, maximum	+70 °C
---	--------

Electrical data

Switching element	see switch description
-------------------	------------------------

Switching principle	see switch description
---------------------	------------------------

Scope of delivery

Included in delivery	Flap profile Latching
----------------------	--------------------------

Delivery scope of Mounting material	Supporting profile Side plates
--	-----------------------------------

Schmersal, Inc., 15 Skyline Drive, Hawthorne, NY 10532

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 11/9/2021, 10:50 AM