



## SET SL 300-1800

- Robust design
- 2 Contacts
- Can be mounted on existing glue-spreading machines, veneering presses, etc.
- Various lengths available

## Data

### Ordering data

eCl@ss number, Version 9.0 27-27-06-90

eCl@ss number, Version 11.0 27-27-06-90

Note (Ordering data) Note: The position switch with safety function is not included in delivery. The following variants can be selected: 1 NO/1 NC T3K 335-11Z-U90 - metal enclosure  
T3K 336-11Z-U90 - thermoplastic enclosure

### General data

|                               |                            |
|-------------------------------|----------------------------|
| Standards                     | EN 60947-5-1               |
| Material of the latching      | Glass-fibre, thermoplastic |
| Material of the profile strip | Aluminium                  |
| Side plate material           | Aluminium                  |
| Gross weight                  | 9,000 g                    |

### Mechanical data - Dimensions

|        |        |
|--------|--------|
| Width  | 100 mm |
| Height | 260 mm |

|             |          |
|-------------|----------|
| Length (L1) | 1,800 mm |
|-------------|----------|

## Ambient conditions

|                      |                  |
|----------------------|------------------|
| Degree of protection | IP67 to EN 60529 |
|----------------------|------------------|

|                                 |        |
|---------------------------------|--------|
| Ambient temperature,<br>minimum | -20 °C |
|---------------------------------|--------|

|                                 |        |
|---------------------------------|--------|
| Ambient temperature,<br>maximum | +55 °C |
|---------------------------------|--------|

|                                               |        |
|-----------------------------------------------|--------|
| Storage and transport<br>temperature, minimum | -20 °C |
|-----------------------------------------------|--------|

|                                               |        |
|-----------------------------------------------|--------|
| Storage and transport<br>temperature, maximum | +70 °C |
|-----------------------------------------------|--------|

## Electrical data

|                   |                        |
|-------------------|------------------------|
| Switching element | see switch description |
|-------------------|------------------------|

|                     |                        |
|---------------------|------------------------|
| Switching principle | see switch description |
|---------------------|------------------------|

## Scope of delivery

|                      |                          |
|----------------------|--------------------------|
| Included in delivery | Flap profile<br>Latching |
|----------------------|--------------------------|

|                                        |                                   |
|----------------------------------------|-----------------------------------|
| Delivery scope of Mounting<br>material | Supporting profile<br>Side plates |
|----------------------------------------|-----------------------------------|

Schmersal, Inc., 15 Skyline Drive, Hawthorne, NY 10532

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 11/9/2021, 10:52 AM