



SHGV/R1.1/x1x+x3x

- Right-hand side locking cylinder
- with two actuating heads
- Aluminium enlosure
- Protection class IP65

Data

Ordering data

Note (Ordering data)

Note: In the order/enquiry, the required key bit numbers "x1x" and the required actuator "x3x" must be indicated (e.g. SHGV/R1.1/115+BO)! If no lock number is indicated in the order/inquiry, we will supply a lock number at our discretion. The user must ensure that lock numbers are not assigned twice in a single plant (factory site)! If no actuator is specified in the order/enquiry, we supply the default actuator BO. The user must ensure that no double key bit numbers are allocated on one site (company site)!

General data

Standards IEC/EN 60947-5-1

Active principle mechanical

Enclosure material Aluminium / chromated steel

Enclosure coating

material

painted

Material of the cylinder lock

Steel

Colour of the

housing

Red

Colour of the key Silver

Colour of key head

Silver

General data - Features

Number of actuating directions

Number of keys 1

Mechanical data

Mechanical life,

100,000 Operations

minimum

Clamping force 1,250 N

Latching force 5 N

Mechanical data - Dimensions

Length 43 mm

Width 87 mm

Height 135 mm

Ambient conditions

Degree of

IP65 to EN 60529

protection

Ambient -25 °C

temperature, minimum

Ambient +70 °C

temperature, maximum

Storage and -40 °C

transport temperature, minimum Storage and transport

temperature, maximum +80 °C

Restistance to

shock

30 g / 18 ms

Resistant to vibration

Resistance to vibration: 15 g / 10...200 Hz

Other data

Note (applications) sliding safety guard

removable guard hinged safety guard

Notes

Note (General) Notice: with two actuating heads for double doors, not for versions "LD" and "RD"

Schmersal, Inc., 15 Skyline Drive, Hawthorne, NY 10532

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 11/9/2021, 11:40 AM