



## SRB200X2

- 2 safety contacts, STOP 0
- Suitable for the signal processing of outputs with contact sensors

## Data

### Ordering data

EAN (European Article Number)	4250116202089
eCl@ss number, Version 9.0	27-37-18-19
eCl@ss number, Version 11.0	27-37-18-19
ETIM number, version 6.0	EC001449
Available until	31.12.2022

### Approval - Standards

Certificates	cULus
	CCC
	EAC

### General data

Standards	IEC 61508 IEC/EN 60204-1 EN 60947-5-1 EN ISO 13849-1
Climatic stress	EN 60068-2-78
Enclosure material	Glass-fibre reinforced thermoplastic, ventilated
Material of the contacts, electrical	AgSn0. self-cleaning, positive drive
Gross weight	230 g

## General data - Features

Stop-Category	0
Electronic Fuse	Yes
Wire breakage detection	Yes
Short-circuit recognition	Yes
Start input	Yes
Feedback circuit	Yes
Reset edge detection	Yes
Earth connection detection	Yes
Integral System Diagnostics, status	Yes
Number of LEDs	3
Number of openers	2
Number of safety contacts	2

## Safety appraisal

Standards	EN 60947-5-1 IEC 61508
-----------	---------------------------

## Safety appraisal - Relay outputs

Performance level, stop 0, up to	e
Category, Stop 0	4
Diagnostic Coverage (DC) Level, Stop 0	$\geq 99\%$
PFH-Value Stop 0	$2.00 \times 10^{-8} /h$
Safety Integrity Level (SIL), Stop 0, suitable for applications in	3
Mission time	20 Year(s)
Common Cause Failure (CCF), minimum	65

### Mechanical data

Mechanical life, minimum	10,000,000 Operations
Mounting	Snap onto standard DIN rail to EN 60715

### Mechanical data - Connection technique

Terminal Connector	Screw connection rigid or flexible
Terminal designations	IEC/EN 60947-1
Cable section, minimum	0.25 mm <sup>2</sup>
Cable section, maximum	2.5 mm <sup>2</sup>
Tightening torque of Clips	0.6 Nm

### Mechanical data - Dimensions

Width	22.5 mm
Height	100 mm
Depth	121 mm

## Ambient conditions

Degree of protection of the enclosure	IP40
Degree of protection of the mounting space	IP54
Degree of protection of clips or terminals	IP20
Ambient temperature, minimum	-25 °C
Ambient temperature, maximum	+60 °C
Storage and transport temperature, minimum	-40 °C
Storage and transport temperature, maximum	+85 °C
Resistance to vibrations to EN 60068-2-6	10 ... 55 Hz, Amplitude 0.35 mm
Resistance to shock	30 g / 11 ms

## Ambient conditions - Insulation value

Rated impulse withstand voltage $U_{imp}$	4 kV
Overvoltage category	III
Degree of pollution to IEC/EN 60664-1	2

## Electrical data

Frequency range	50 Hz 60 Hz
Rated operating voltage	24 VAC -15% / +10% 24 VDC -15%/+20%, residual ripple max. 10%
Rated AC voltage for controls, 50 Hz, minimum	20.4 VAC

Rated control voltage at AC 50 Hz, maximum	26.4 VAC
Rated AC voltage for controls, 60 Hz, minimum	20.4 VAC
Rated control voltage at AC 60 Hz, maximum	26.4 VAC
Rated AC voltage for controls at DC minimum	20.4 VDC
Rated control voltage at DC, maximum	28.8 VDC
Electrical power consumption	1.5 W
Electrical power consumption	3 VA
Contact resistance, maximum	0.1 $\Omega$
Note (Contact resistance)	in new state
Drop-out delay in case of power failure, typically	80 ms
Drop-out delay in case of emergency, typically	20 ms
Pull-in delay at automatic start, maximum, typically	100 ms
ON delay at automatic start	Adjustable
Pull-in delay at RESET, typically	20 ms

### Electrical data - Safe relay outputs

Voltage, Utilisation category AC15	250 VAC
Current, Utilisation category AC-15	6 A
Voltage, Utilisation category DC13	24 VDC

Current, Utilisation category DC13	6 A
Switching capacity, minimum	10 VDC
Switching capacity, minimum	10 mA
Switching capacity, maximum	250 VAC
Switching capacity, maximum	8 A

### Electrical data - Digital inputs

Conduction resistance, maximum	40 $\Omega$
--------------------------------	-------------

### Electrical data - Relay outputs (auxiliary contacts)

Switching capacity, maximum	24 VDC
Switching capacity, maximum	2 A

### Electrical data - Electromagnetic compatibility (EMC)

EMC rating	EMC-Directive
------------	---------------

### Status indication

Indicated operating states	Position relay K2 Position relay K1
----------------------------	--

### Other data

Note (applications)	Guard system Emergency-Stop button Pull-wire emergency stop switches
---------------------	--

## Notes

Note (General) Inductive loads (e.g. contactors, relays, etc.) are to be suppressed by means of a suitable circuit.

## Circuit example

Note (Wiring diagram) The wiring diagram is shown with guard doors closed and in de-energised condition. If only one external relay or contactor is used to switch the load, the system can be classified in Control Category 3 to ISO 13849-1, if exclusion of the fault "Failure of the external contactor" can be substantiated and is documented, e.g. by using a reliable down-rated contactor. A second contactor leads to an increase in the level of security by redundant switching to switch the load off.  
To secure a guard door up to PL e and Category 4  
The feedback circuit monitors the positions of the positive-guided NC contacts on the conactors Ka and Kb.

Schmersal, Inc., 15 Skyline Drive, Hawthorne, NY 10532

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 11/9/2021, 8:44 AM