DATASHEET





V-SK8P-M12/M8-S-G-0,5M-BK-2-X-A-4

Data

Ordering data

EAN (European Article Number) 4030661463834
eCl@ss number, Version 9.0 27-06-03-11
eCl@ss number, Version 11.0 27-06-03-11
ETIM number, version 6.0 EC001855
ETIM number, version 7.0 EC001855

General data

Standards IEC 61076-2-101

Gross weight 49.1 g

General data - Features

Halogen free Yes (1)
Cable drag chain suitable Yes (1)
Number of poles 8
Number of cable wires 8

Mechanical data

Tightening torque, maximum

1 Nm

Mechanical data - Connection technique

Length of cable 0.5 m

Wire cross-section 0.25 mm²

Cable diameter 6 mm

Bending radius (fixed) 5 x Ø-cable

Bending radius (repeated) 10 x Ø-cable

Colour of the Cable mantle Black

Material of the Cable mantle PUR

Mechanical data - connector side A

Connector typ Female connector, M8

Design straight

Connector coding A

Connector latching Screw locking

Material of the gland Metal, CuZn, nickel-plated

Material of the handle Plastic, TPU

Colour of the handle Black

Mechanical data - connector side B

Connector typ Male connector, M12

Design straight

Connector coding A

Connector latching Screw locking

Material of the gland Metal, CuZn, nickel-plated

Material of the handle Plastic, TPU

Colour of the handle Black

Ambient conditions	
Degree of protection	IP67
Ambient temperature, minimum (Connector)	-25 °C
Ambient temperature, maximum (Connector)	+85 °C
Temperature (fixed), minimum	-50 °C
Temperature (fixed), maximum	+90 °C
Temperature (repeated), minimum	-25 °C
Temperature (repeated), maximum	+90 °C

Electrical data	
Thermal test current	1.5 A
Rated operating voltage	30 V
Operating current	1,500 mA

Pin assignment	
PIN 1	White
PIN 2	Brown
PIN 3	green
PIN 4	yellow
PIN 5	Grey
PIN 6	Pink
PIN 7	Blue
PIN 8	red

Schmersal, Inc., 15 Skyline Drive, Hawthorne, NY 10532

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 11/9/2021, 9:52 AM