



BN 32-11R

- Non-contact principle
- 1 Reed kontakts
- Long life
- Actuating surface and direction of actuation marked by switch symbol
- 85 mm x 26 mm x 24 mm
- Thermoplastic enclosure
- Actuating distance up to 55 mm depending on actuating magnet and version
- Spade connector

Data

Ordering data

EAN (European Article Number)	4030661025520
eCl@ss number, Version 9.0	27-27-01-05
eCl@ss number, Version 11.0	27-27-01-05
ETIM number, version 6.0	EC002544
ETIM number, version 7.0	EC002544

General data

Active principle	Magnetic drive
Housing construction form	Block
Enclosure material	Glass-fibre, reinforced thermoplastic
Active area	Plastic
Gross weight	62 g

General data - Features

Latching	Yes
----------	-----

Mechanical data

Actuating panels	lateral
Active area	lateral
Actuating element	Magnet
Mechanical life, minimum	1,000,000,000 Operations
Repeat accuracy R R	0.3 mm
Actuating speed, maximum	18 m/s

Mechanical data - Switching distances according IEC 60947-5-3

Switch distance S_n	5 mm ... 55 mm
	2 x BP 21S = 20 ... 55 mm
	BP 34S = 10 ... 25 mm
	BP 10N = 10 mm
	BP 10S = 10 mm
	2 x BP 10N = 15 mm
	2 x BP 10S = 15 mm
	BP 15N = 12 mm
	BP 15S = 12 mm
	2 x BP 15/2N = 17 mm
	2 x BP 15/2S = 17mm
	BP 34N = 10 ... 25mm
	BP 20N = 5 ... 20 mm
	BP 20S = 5 ... 20 mm
	BP 31N = 5 ... 20 mm
	BP 31S = 5 ... 20 mm
	BP 11N = 10 mm
	BP 11S = 10 mm
	2 x BP 11N = 20 mm
	2 x BP 11S = 20 mm
	BP 12N = 15 mm
	BP 12S = 15 mm
	2 x BP 12N = 10 ... 25 mm
	2 x BP 12S = 10 ... 25 mm
	BP 21N = 15 ... 40 mm
	BP 21S = 15 ... 40 mm
	2 x BP 21N = 20 ... 55 mm
	BE 20N = 15 mm
	BE 20S = 15 mm

Notice (Switch distance S_n) Actuating distance up to 55 mm depending on version and actuating magnet

Mechanical data - Connection technique

Terminal Connector Flat plug-in connector 4.8 mm

Mechanical data - Dimensions

Length of sensor	24 mm
Width of sensor	85 mm
Height of sensor	26 mm

Ambient conditions

Degree of protection	IP67
Ambient temperature, minimum	-25 °C
Ambient temperature, maximum	+90 °C
Resistant to vibration	15 g, on sine wave oscillation

Electrical data

Voltage type	AC (alternating current)
Switching voltage, maximum	220 VAC
Switching current, maximum	1 A
Switching capacity, maximum	60 W
Switching capacity, maximum	60 VA
Switching element	NO contact / NC contact
Bounce duration, minimum	0.3 ms
Bounce duration, maximum	0.6 ms
Switching frequency	720,000 /h

Electrical data - Digital Output

Versions	Reed contacts
----------	---------------

Scope of delivery

Included in delivery	Actuators must be ordered separately.
----------------------	---------------------------------------

Accessory

Recommendation (actuator)	BP 10 S
	2x BP 10 S
	BP 15 S
	BP 34 S
	BP 20 S
	BP 31 S
	BP 11 S
	2x BP 11 S
	BP 12 S
	BP 21 S
	2x BP 21 S
	BE 20 S
	BP 10 N
	2x BP 10 N
	BP 15 N
	2 x BP 15/2 N
	2x BP 15/2 S
	BP 34 N
	BP 20 N
	BP 31 N
	BP 11 N
	2x BP 11 N
	BP 12 N
	2x BP 12 N
	2x BP 12 S
	BP 21 N
	2x BP 21 N
	BE 20 N

Notes

Note (General)

The opening and closing functions depend on the direction of actuation, the actuating magnets and the polarity of the actuating magnets.

Schmersal, Inc., 15 Skyline Drive, Hawthorne, NY 10532

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 11/9/2021, 8:58 AM