



BN 85-5-2031

- Enclosure with mounting slots
- Actuation from front
- Non-contact principle
- 5 reed contacts
- Long life
- LED switching conditions display
- connector
- Thermoplastic enclosure
- Reed-contact to clip-in, on-location assembly

Data

Ordering data

EAN (European Article Number)	4030661050058
eCl@ss number, Version 9.0	27-27-01-05
eCl@ss number, Version 11.0	27-27-01-05
ETIM number, version 6.0	EC002544
ETIM number, version 7.0	EC002544

General data

Active principle	Magnetic drive
Housing construction form	rectangular
Enclosure material	Glass-fibre, reinforced thermoplastic
Gross weight	106 g

General data - Features

Latching	Yes
Suitable for elevators	Yes
Integral System Diagnostics, status	Yes
Number of Snap-in contacts, maximum	5
Number of Snap-in contacts, minimum	1

Mechanical data

Actuating panels	front side
Actuating element	Magnet
Mechanical life, minimum	1,000,000,000 Operations
Mounting	Enclosure with mounting slots

Mechanical data - Switching distances according IEC 60947-5-3

Switch distance S_n	1 mm ... 14 mm
Notice (Switch distance S_n)	The specified switching distances are applicable for the actuation of individually mounted components without ferromagnetic influence. A change of the distance, either positive or negative, is possible due to ferromagnetic influences. The mutual interference between multiple actuating magnets must be observed.

Mechanical data - Connection technique

Terminal Connector	Connector, 10-pole
--------------------	--------------------

Mechanical data - Dimensions

Length of sensor	140 mm
Width of sensor	65 mm
Height of sensor	20 mm

Ambient conditions

Degree of protection	IP30 to EN 60529
Ambient temperature, minimum	-10 °C
Ambient temperature, maximum	+75 °C
Resistance to shock	60 g, on sine wave oscillation

Electrical data

Switching voltage, minimum	12 VDC
Switching voltage, maximum	60 VDC
Switching current, maximum	1 A
Switching capacity, maximum	30 W
Switching element	bistable contact

Electrical data - Digital Output

Versions	Reed contacts
----------	---------------

Scope of delivery

Included in delivery	Actuators must be ordered separately.
----------------------	---------------------------------------

Accessory

Recommendation (actuator)	BP 7
Recommendation (actuator, lift switchgear)	BP 7

Notes

Note (General) The opening and closing functions depend on the direction of actuation, the actuating magnets and the polarity of the actuating magnets.

Schmersal, Inc., 15 Skyline Drive, Hawthorne, NY 10532

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 11/9/2021, 9:03 AM