



EX-RSS16-D-R-10M-3G/D

- Door stop with magnetic latching
- Explosion protection for ATEX Zones 2 and 22
- Thermoplastic enclosure
- RFID-technology for needs-based protection against tampering
- 3 different directions of actuation

Data

Ordering data

EAN (European Article Number)	4030661530581
eCl@ss number, Version 9.0	27-27-24-01

Approval - Standards

Certificates	TÜV
--------------	-----

General data

Housing construction form	Block
Gross weight	250 g

Mechanical data

Active area	lateral front side cover-side
-------------	-------------------------------------

Mechanical data - Switching distances according IEC 60947-5-3

Switch distance	15 mm
Ensured switch distance "ON" S_{ao}	12 mm
Ensured switch distance "OFF" S_{ar}	30 mm

Ambient conditions

Degree of protection	IP65 to EN 60529 IP67 to EN 60529
----------------------	--------------------------------------

Accessory

Recommendation (actuator)	RST16-1-R
Recommended safety switchgear	PROTECT PSC1 SRB-E-301ST SRB-E-201LC

Schmersal, Inc., 15 Skyline Drive, Hawthorne, NY 10532

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 11/9/2021, 9:45 AM