



## ZS 232-11 SOCKEL KPL.

- Thermoplastic enclosure
- Changeover contact with double break, positive break
- galvanically separated contact bridges
- Screw connection

## Data

### Ordering data

EAN (European Article Number) 4030661100456

### General data

Standards	IEC/EN 60947-5-1
Terminal (mechanical)	Screw connection
Enclosure material	Glass-fibre, reinforced thermoplastic
Material of the actuator	Stainless steel
Material of the contacts, electrical	Silver
Gross weight	23.8 g

### General data - Features

Number of openers	1
Number of shutters	1

## Mechanical data

Mechanical life, minimum	20,000,000 Operations
Actuating force	9 N
Actuating speed	10 mm/min

## Mechanical data - Connection technique

Cable section, maximum	2.5 mm <sup>2</sup>
------------------------	---------------------

## Ambient conditions

Degree of protection	IP40
Degree of protection of clips or terminals	IP00 (without connector)
Ambient temperature, minimum	-30 °C
Ambient temperature, maximum	+80 °C

## Ambient conditions - Insulation value

Rated insulation voltage $U_i$	500 V
Rated impulse withstand voltage $U_{imp}$	6 kV
Degree of pollution to VDE 0100	3

## Electrical data

Thermal test current	10 A
Utilisation category AC-15	230 VAC
Utilisation category AC-15	4 A
Switching principle	Snap action

Schmersal, Inc., 15 Skyline Drive, Hawthorne, NY 10532

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 11/9/2021, 9:29 AM