DATASHEET





TV10H 016-30Y

- 3 Cable entry M 20 x 1.5
- Metal enclosure
- 3 Contacts
- 67 mm x 105 mm x 43 mm (basic component)
- Actuator head can be repositioned in steps 4 x 90°
- Continuous adjustment of lever position 360°
- Lever can be transposed by 180°
- Epoxy resin rod

Data

Ordering data

eCl@ss number, Version 9.0 27-27-06-01

eCl@ss number, Version 11.0 27-27-06-01

ETIM number, version 6.0 EC000030

ETIM number, version 7.0 EC000030

General data

Standards EN 60947-5-1

Active principle mechanical

Enclosure material Light-alloy diecast, paint finish

Enclosure coating material painted

Material of the contacts, electrical Silver

Material of the rod Epoxy resin

Gross weight 470 g

General data - Features

Number of shutters 3

Mechanical data

Actuating element Rod lever

Mechanical life, minimum 5,000,000 Operations

Actuating angle, from left of switch axis 30 °

Actuating angle, from right of switch axis 30 °

Contact opening 2 x 2.5 mm

Actuating speed, minimum 1 mm/min

Actuating speed, maximum 3 m/s

Note (Actuating speed) Actuating speed with vertical actuating angle to switch axis

Actuating torque 0.3 Nm

Mechanical data - Connection technique

Terminal Connector Screw connection

Cable section, minimum 1.5 mm²

Cable section, maximum 2.5 mm²

Note (Cable section) All indications about the cable section are including the conductor

ferrules.

Wire cross-section 13 AWG

Mechanical data - Dimensions

Length of sensor 43 mm

Width of sensor 67 mm

Height of sensor 286 mm

Diameter of the Rod 6 mm

Ambient conditions

Degree of protection IP65 to EN 60529

Ambient temperature, minimum -30 °C

Ambient temperature, maximum +90 °C

Ambient conditions - Insulation value

Rated insulation voltage U_i 400 V

Electrical data

Thermal test current 10 A

Utilisation category AC-15 400 VAC

Utilisation category AC-15 4 A

Switching element Normally open contact (NO)

Note (Switching element) with double break

Switching principle Creep circuit element

Schmersal, Inc., 15 Skyline Drive, Hawthorne, NY 10532

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 11/9/2021, 9:13 AM