

ÖLFLEX® CLASSIC 115 CY

Screened PVC control cable with small outer diameter



Info

- CPR: Article number choice under www.lappkabel.com/cpr
- Thin and light, without inner sheath
- EMC-compliant

LAPP KABEL STUFGART ÖLFLEX® CLASSIC 115 CY 7 G 1,5 CE



Technical data



Classification ETIM 5/6

ETIM 5.0/6.0 Class-ID: EC000104
ETIM 5.0/6.0 Class-Description:
Control cable



Core identification code

Black with white numbers acc. to
VDE 0293-1



Conductor stranding

Fine wire according to VDE 0295,
class 5/IEC 60228 class 5



Minimum bending radius

Occasional flexing: 20 x outer diameter
Fixed installation: 6 x outer diameter



Nominal voltage

U0/U: 300/500 V



Test voltage

Core/core: 4000 V
Core/screen: 2000 V



Protective conductor

G = with GN-YE protective conductor
X = without protective conductor



Temperature range

Occasional flexing: -5°C to +70°C
Fixed installation: -40°C to +80°C

Benefits

- Space-saving installation due to small cable diameters

Application range

- Measurement and control technology
- Office machines and systems for data processing

Product features

- Flame-retardant according IEC 60332-1-2
- Good chemical resistance, see catalogue appendix T1
- High degree of screening
low transfer impedance
(max. 250 Ω/km at 30 MHz)

Norm references / Approvals

- Based on EN 50525-2-51

Product Make-up

- Fine-wire strand made of bare copper wires
- PVC insulation LAPP P8/1
- Cores twisted in layers
- Plastic foil wrapping
- Tinned-copper braiding
- PVC outer sheath, grey (similar RAL 7001)

Article number	Number of cores and mm ² per conductor	Outer diameter [mm]	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® CLASSIC 115 CY				
1136752	2 X0,5	5.8	36	45
1136003	3 G0,5	6.1	43	59
1136753	3 X0,5	6.1	43	59
1136004	4 G0,5	6.5	49	71
1136754	4 X0,5	6.5	49	71
1136005	5 G0,5	7.0	57	86
1136755	5 X0,5	7.0	57	86
1136007	7 G0,5	7.5	69	105
1136757	7 X0,5	7.5	69	105
1136012	12 G0,5	9.9	104	200
1136762	12 X0,5	9.9	104	200
1136018	18 G0,5	11.5	141	275
1136768	18 X0,5	11.5	141	275
1136025	25 G0,5	13.4	211	350
1136775	25 X0,5	13.4	211	350
1136802	2 X0,75	6.2	43	56
1136103	3 G0,75	6.5	52	70
1136803	3 X0,75	6.5	52	70
1136104	4 G0,75	7.0	61	95
1136804	4 X0,75	7.0	61	95
1136105	5 G0,75	7.7	72	108
1136805	5 X0,75	7.7	72	108
1136107	7 G0,75	8.3	89	127
1136807	7 X0,75	8.3	89	127
1136112	12 G0,75	10.9	138	232
1136118	18 G0,75	12.7	211	315
1136125	25 G0,75	14.8	280	435
1136825	25 X0,75	14.8	280	435
1136852	2 X1,0	6.5	51	71
1136203	3 G1,0	6.8	62	86
1136853	3 X1,0	6.8	62	86
1136204	4 G1,0	7.3	74	98
1136854	4 X1,0	7.3	74	98
1136205	5 G1,0	8.1	88	121
1136855	5 X1,0	8.1	88	121

Article number	Number of cores and mm ² per conductor	Outer diameter [mm]	Copper index (kg/km)	Weight (kg/km)
1136207	7 G1,0	8.8	112	147
1136857	7 X1,0	8.8	112	147
1136212	12 G1,0	11.5	185	285
1136218	18 G1,0	13.9	268	395
1136225	25 G1,0	15.9	354	486
1136902	2 X1,5	7.1	65	86
1136303	3 G1,5	7.5	82	112
1136903	3 X1,5	7.5	82	112
1136304	4 G1,5	8.2	100	135
1136904	4 X1,5	8.2	100	135
1136305	5 G1,5	8.9	119	148
1136905	5 X1,5	8.9	119	148
1136307	7 G1,5	9.9	154	192
1136907	7 X1,5	9.9	154	192
1136312	12 G1,5	13.0	268	365
1136318	18 G1,5	15.6	373	520
1136325	25 G1,5	17.9	530	734
1136334	34 G1,5	20.8	683	944
1136403	3 G2,5	8.9	118	151
1136404	4 G2,5	9.9	147	188
1136405	5 G2,5	11.0	176	270
1136407	7 G2,5	11.9	253	340
1136412	12 G2,5	16.0	355	540
1136418	18 G2,5	19.0	569	782
1136425	25 G2,5	22.2	827	1358
1136504	4 G4	11.6	248	305
1136507	7 G4	14.4	355	500
1136604	4 G6	14.2	343	440
1136607	7 G6	17.0	505	672
1136614	4 G10	17.2	495	680
1136615	5 G10	19.5	592	824
1136624	4 G16	20.2	800	1050
1136625	5 G16	22.6	895	1285
1136634	4 G25	25.1	1075	1413
1136635	5 G25	28.0	1400	1976
1136638	4 G35	28.0	1576	2070

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.

Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths / Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum

Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Similar products

- ÖLFLEX® ROBUST 215 C refer to page 72
- ÖLFLEX® CLASSIC 110 CY refer to page 41

Accessories

- SKINTOP® BRUSH ADD-ON refer to page 700
- 3M Scotch™ 1183 screening tape refer to page 1030
- SKINTOP® MS-HF-M BRUSH refer to page 708
- SKINTOP® MS-M BRUSH refer to page 702