


90° Non-Metallic Connectors

For use with non-metallic liquid-tight conduit, type B only. 90° connector provides a smooth, gradual radius bend. Wiring is easily pulled or pushed through fitting and there are no sharp edges to strip wire. Produced from UV rated plastic for long outdoor life.

CATALOG NUMBER	UPC/DCI/NAED MFG #018997	TRADE SIZE	KO SIZE	UNIT PKG	STD PKG	DIM A	DIM B	DIM C
NMLT9038	54903	3/8	1/2	10	50	2.305	.562	2.460
NMLT9050	54905	1/2	1/2	10	50	2.242	.562	2.460
NMLT9075	54907	3/4	3/4	10	50	2.550	.545	2.840
NMLT90100	54901	1	1	5	25	3.150	.630	3.680
NMLT90125	54912	1-1/4	1-1/4	5	25	3.420	.645	4.650
NMLT90150	54915	1-1/2	1-1/2	2	10	4.510	.660	4.470
NMLT90200	54920	2	2	2	10	4.850	.670	5.290



Add suffix "BL" to Catalog # when ordering in black, for example NMLT9050BL.



45° Non-Metallic Connectors

For use with non-metallic liquid-tight conduit, type B only. 45° connector provides a smooth, gradual radius bend. Wiring is easily pulled or pushed through fitting and there are no sharp edges to strip wire. Produced from UV rated plastic for long outdoor life.

CATALOG NUMBER	UPC/DCI/NAED MFG #018997	TRADE SIZE	KO SIZE	UNIT PKG	STD PKG	DIM A	DIM B	DIM C
NMLT4538	54538	3/8	1/2	10	50	1.603	.538	1.891
NMLT4550	54550	1/2	1/2	10	50	1.588	.540	1.918
NMLT4575	54575	3/4	3/4	10	50	1.840	.545	2.243
NMLT45100	54110	1	1	5	25	2.200	.704	2.921
NMLT45125	54125	1-1/4	1-1/4	5	25	2.710	.662	3.240
NMLT45150	54150	1-1/2	1-1/2	2	10	2.960	.653	3.675
NMLT45200	54200	2	2	2	10	3.500	.689	4.060



Add suffix "BL" to Catalog # when ordering in black, for example NMLT4550BL.

