

With spring steel clip. For NM • SE • MCI • MCIA • Flex • AC cable. For steel and aluminum jacketed cables. Zinc die-cast.

(See page E-1 for ring removal instructions.)

CATALOG NUMBER	UPC/DCI/NAED MFG #018997	TRADE SIZE	KO SIZE	UNIT PKG	STD PKG	DIM A	DIM B	DIM C	CABLE RANGE
840ST	80070	3/8	1/2	100	1000	.420	.880	.876	.225 - .612
8400ST	80074	3/8	1/2	100	1000	.420	.880	.876	.225 - .612





SNAP-TITE® products have been tested and listed by UL in accordance with UL's ground fault requirements.

For additional information, see page 7.


Refer to pages C-13 and C-14 for complete cable ranges.

For connectors that cost less and install faster, see page C-8.

PATENTED



840ST



8400ST



840ST




8400ST

NM Cable Connector

For NM cable. Zinc die-cast.

CATALOG NUMBER	UPC/DCI/NAED MFG #018997	TRADE SIZE	KO SIZE	UNIT PKG	STD PKG	DIM A	DIM B	DIM C	CABLE RANGE
841	00841	3/8	1/2	100	1000	.400	.865	1.106	.225 - .612



Refer to pages C-13 and C-14 for complete cable ranges.
For connectors that cost less and install faster, see page C-8



SNAP-TITE® Connector

With spring steel clip. For NM cable. Zinc die-cast.

(See page E-1 for ring removal instructions.)

CATALOG NUMBER	UPC/DCI/NAED MFG #018997	TRADE SIZE	KO SIZE	UNIT PKG	STD PKG	DIM A	DIM B	DIM C	CABLE RANGE
841ST	80068	3/8	1/2	100	1000	.420	.880	.920	.225 - .612



SNAP-TITE® products have been tested and listed by UL in accordance with UL's ground fault requirements.

For additional information, see page 7.

Refer to pages C-13 and C-14 for complete cable ranges.

PATENTED.

