


Rigid conduit/IMC fittings

Bushings (continued)


Insulated bushings – iron/zinc plated



Cat. No.	Conduit Size (in.)	Dimensions (in.)		Std. Ctn.
		A	B	
BI-901	1/2	1 1/32	1/2	1,000
BI-902	3/4	1 1/4	1/2	1,000
BI-903	1	1 9/16	9/16	500
BI-904	1 1/4	1 15/16	19/32	200
BI-905	1 1/2	2 13/64	5/8	100
BI-906	2	2 45/64	5/8	50
BI-907	2 1/2	3 7/32	9/16	30
BI-908	3	3 27/32	9/16	25
BI-909	3 1/2	4 7/16	7/8	25
BI-910	4	4 31/32	2 9/32	25



UL File No. E-23018.



Insulated grounding bushings – malleable iron/zinc plated –



Cat. No.	Trade Size (in.)	Grounding Lug Wire Capacity	Dimensions (in.)		Std. Ctn.
			A	B	
BG801L	1/2	–	1 1/32	1/2	500
BG802L	3/4	#14–#4 CU	1 1/4	1/2	500
BG803L	1	or	1 9/16	9/16	250
BG804L	1 1/4	#12–#4 AL	1 15/16	19/32	150
BG805L	1 1/2	–	2 13/64	5/8	150
BG806L	2	–	2 45/64	5/8	100
BG807L	2 1/2	#14–1/0 CU	3 3/16	9/16	60
BG808L	3	or #12–1/0 AL	3 5/8	9/16	30
BG809L	3 1/2	#6–250 kcmil	4 1/16	7/8	30
BG810L	4	CU or AL	4 21/32	2 9/32	30

UL File No. E-3060.

1/2" Iron, 2 1/2"-4" – die-cast zinc.

Features and benefits:

- For copper or aluminum bare ground wire
- 105° C thermoplastic liners
- Heavy reinforced ribs

Grounding bushings – malleable iron/zinc plated – Insulated with Aluminum lug



Cat. No.	Conduit Size (in.)	Grounding Lug Wire Size		Std. Ctn.
		Min.	Max.	
BG-801A	1/2	14 AWG	6 AWG	500
BG-802A	3/4	14 AWG	6 AWG	500
BG-803A	1	14 AWG	6 AWG	250
BG-804A	1 1/4	14 AWG	2 AWG	200
BG-805A	1 1/2	14 AWG	2 AWG	100
BG-806A	2	14 AWG	2 AWG	100
BG-807A	2 1/2	14 AWG	2/0 AWG	50
BG-808A	3	14 AWG	2/0 AWG	50
BG-809A	3 1/2	14 AWG	2/0 AWG	10
BG-810A	4	14 AWG	2/0 AWG	10
BG-810B	4	6 AWG	250 kcmil	10

UL File No. E-3060.

Features and benefits:

- RB-121 thru RB-165 – steel
- RB-175 thru RB-187 – malleable iron (concrete tight), zinc plated

Reducing bushings



Cat. No.	Conduit Size (in.)	Dimensions (in.)		Std. Ctn.
		A	B	
RB 121	3/4-1/2	9/16	7/8	100
RB-131	1-1/2	5/8	1 1/8	50
RB-132	1-3/4	5/8	1 1/8	50
RB-141	1 1/4-1/2	11/16	17/16	50
RB 142	1 1/4-3/4	11/16	17/16	50
RB-143	1 1/4-1	11/16	17/16	50
RB-151	1 1/2-1/2	23/32	1 11/16	50
RB-152	1 1/2-3/4	23/32	1 11/16	50
RB-153	1 1/2-1	23/32	1 11/16	50
RB-154	1 1/2-	23/32	1 11/16	50
RB-161	2-1/2	27/32	2 3/32	25
RB-162	2-3/4	27/32	2 3/32	25
RB-163	2-1	27/32	2 3/32	25
RB-164	2-1 1/4	27/32	2 3/32	25
RB-165	2-1 1/2	27/32	2 3/32	25
RB-175	2 1/2-	7/8	2 13/16	25
RB-176	2 1/2-2	7/8	2 13/16	25
RB-186	3-2	29/32	2 7/16	25
RB-187	3-2 1/2	29/32	2 7/16	25

UL File No. E-23018.