


Concrete/masonry boxes and accessories

Gangable masonry boxes



GW 135 G



GW 235 G

Gangable masonry boxes




Cat. No.	Depth (in.)	Height (in.)	Length (in.)	Capacity (cu. in.)	Eccentric Knockouts 1/2" & 3/4"			Std. Ctn.
					Each side	Each end	Bottom	
With eccentric conduit KOs								
GW 125 G*	2½	3¾	1 ¹⁵ / ₁₆	15.0	2	2	2	20
GW 225 G*	2½	3¾	3¾	31.6	2	4	4	10
GW 325 G*	2½	3¾	5 ⁹ / ₁₆	47.4	2	6	6	5
GW 425 G	2½	3¾	7 ³ / ₈	64.0	2	8	8	5
GW 525 G	2½	3¾	9 ³ / ₁₆	79.0	2	10	10	5
GW-625-G*	2½	3¾	11	94.8	2	12	12	1
GW 135 G*	3½	3¾	1 ¹⁵ / ₁₆	22.0	4	2	2	20
GW 235 G*	3½	3¾	3¾	46.9	4	4	4	10
GW 335 G	3½	3¾	5 ⁹ / ₁₆	71.0	4	6	6	10
GW 435 G*	3½	3¾	†7 ³ / ₈	93.5	4	8	8	5
GW-535-G	3½	3¾	†9 ³ / ₁₆	111.7	4	10	10	5
GW-635-G	3½	3¾	*†11	134.0	4	12	12	1

* Per NEC®, suitable for use without a bonding jumper in circuits above or below 250 volts.
† 4-, 5- and 6-gang supplied with partitions.

Masonry box partitions

Masonry box partitions



		Cat. No.	Description	Std. Ctn.
		PGW-25-G	Non-metallic partition for 2 1/2"-deep steel tile wall boxes	25
		PGW-35-G	Non-metallic partition for 3 1/2"-deep steel tile wall boxes	25

PGW-25-G

PGW-35-G