

4.8 in

PRODUCT-DETAILS

Package Level 1 Height

## IKL35

## AL SERV ENTR SPLICE A:1/0 B:1-2 5.5



Extended Product Type	IKL35
Product ID	7TAA267180R0029
EAN	0783786050215
Catalog Description	AL SERV ENTR SPLICE A:1/0 B:1-2 5.5
Long Description	Aluminum 4 inch Service Entrance Compression Splice for Wire Range - Yellow End: 1/0 ASCR, 1/0 STR, 2/0 CPT, 1/0 CPR. Red End: #2 ASCR, #1 STR, #1 SOL, #1 CPR. Installing Dies: TX 249 840 (EEI 11A). Compound and Capped. includes 5-7/16 inch Sleeve
Ordering	
EAN	0783786050215
Dimensions	
<b>Dimensions</b> Product Net Weight	.227 lb 102.948 g
	··
	·· ··-
Product Net Weight	102.948 g
Product Net Weight  Container Information	.227 lb 102.948 g 25 piece 6.9 in

	122 mm
Package Level 1 Depth / Length	7.4 in 188 mm
Package Level 2 Units	100 piece
Package Level 2 Width	10.1 in 257 mm
Package Level 2 Height	8.3 in 211 mm
Package Level 2 Depth / Length	14.2 in 361 mm

Additional Information	
Application	For Combinations of Aluminum-to-Aluminum and Aluminum-to-Copper Conductors. Use as a low tension reducing sleeve for Insulated Conductor.
Brand / Label	Blackburn
Connection Type	Compression
Insulation Material	Yes
Material	Aluminum
Mounting Type	None
Number of Batteries	0
Number of Conductors	2
Product Name	BKB-OVERHEAD SPLICE & TAP CONN
Product Type	Compression Splice Service Entrance
Size	Splice 4 inch, Sleeve 5-1/2 inch
Special Functions	Pre-insulated for fast, easy installation of large home or commercial service entrances. Concave polyethylene end caps seal out dirt, but are easily pierced when inserting conductor.
Standards	RUS Listed. Passes the Requirements of ANSI C119.4
UPC	783786050215

Certificates and Declarations (Document Number)		
Data Sheet, Technical Information	IKL35	
Instructions and Manuals	IKL35	

Classifications		
UNSPSC	39121449	
WEEE Category	Product Not in WEEE Scope	
IDEA Granular Category Code (IGCC)	4669 >> Wire or cable compression splice	

## Categories

IKL35 3

