

Bushings, nipples, locknuts and plugs

Insulated throat fittings and metallic bushings




- Meets and surpasses NEC® requirements
- Steel or malleable iron (steel through 1½")
- Exceeds NEC 373-6C requirements for protection of ungrounded connectors at entrance to raceways, pull boxes and junctions
- Recognizable by distinctive trademarked blue insulating liner in throat
- Reduces wire pulling effort by as much as 50%
- Temperature rating of 105 °C
- Look for the unique blue color, ensuring the highest quality fitting

- Locknut-type base improves bonding and resists loosening under vibration.
- Aluminum, steel or malleable iron (steel through 1½")
- Smoothly rounded shoulder covers end of conduit
- Broad flange covers knockout hole
- High ribs for easy tightening with fingers or with wrench
- ½" to 1½" sizes, formed in steel, feature extra-smooth shoulders

Insulated throat fittings

Cat. no.	Dimensions (in.)			
	Steel or M.I.	Alum.	Size (in.)	
1222		1222AL	½	1 1/32 29/64
1223		1223AL	¾	1 9/32 31/64
1224		1224AL	1	1 19/32 11/32
1225		1225AL	1 ¼	1 15/16 21/32
1226		1226AL	1 ½	2 3/16 23/32
1227		1227AL	2	2 11/16 7/8
1228		1228AL	2 ½	3 3/16 1/32
1229		1229AL	3	3 27/32 5/16
1230		1230AL	3 ½	4 7/16 1 1/16
1231		1231AL	4	4 7/8 1 3/32
1232†		1232AL†	4 ½	– –
586		586AL	5	5 31/32 1 9/32
587		587AL	6	7 3/16 1 11/32

Diagram




Nylon insulated
metallic bushings

Metallic bushings



Cat. no.	Dimensions (in.)			
	Steel or M.I.	Alum.	Size (in.)	
122		122AL	½	1 1/32 13/32
123		123AL*	¾	1 ¼ 7/16
124		124AL**	1	1 9/16 ½
125-TB		125AL	1 ¼	1 29/32 9/16
126		126AL	1 ½	2 5/32 19/32
127		127AL	2	2 21/32 5/8
128		128AL	2 ½	3 3/16 ¾
129		129AL	3	3 27/32 13/16
130-TB		130AL	3 ½	4 3/8 1 5/16
131-TB		131AL	4	4 15/16 1
132-TB		–	4 ½	5 7/16 1 5/64
133-TB		133AL	5	6 1 3/16
134-TB		134AL	6	7 ¼ 1 ¼

Diagram



† Not CSA certified
Catalog series 1222 through 1232, 586 and 587 are available in aluminum.
Add suffix AL to cat. no. The aluminum series fittings are not CSA certified.

* Not UL listed or CSA certified
** Not CSA certified
Available with DURA-PLATE® finish.
UL File No. E-23018
CSA File No. 2884