



Molded Case Circuit Breakers

Quick Reference Guide



THQL 32015

Ratings do not apply to molded case switches.

The interruption ratings and voltages shown in the table are maximum ratings. A circuit breaker of the type given in the lefthand column may be applied at the given circuit voltage in any electrical distribution system where the available fault current at the load terminals of the breaker does not exceed the value in the table. That circuit breaker type may also be applied at intermediate values of circuit voltage provided the available fault current at the load terminals of the breaker does not exceed the value in the table for the higher value of voltage.

Q-Line (UL file E-11592; Fixed Thermal Magnetic Trip Unit)

Circuit Breaker Type	Ampere Rating	No. Poles	Maximum Voltage Rating	UL Listed Interrupting Ratings—rms Symmetrical kA										Dimensions (in.)							Std. Pack
				ac	dc	120	120/240	240	277	480	600	125	250	H	W	D	A	B	C	E	
TQ	15-50	1	120/240	—	—	10	—	—	—	—	—	—	—	3	3/4	2 3/8	—	—	—	—	10
	15-60	2	120/240	—	—	10	—	—	—	—	—	—	—	3	1 1/2	2 3/8	—	—	—	—	5
THQP ¹	15-50	1	120/240	—	—	10	—	—	—	—	—	—	—	3 9/32	1 1/2	2 3/8	—	—	—	—	100
		2	120/240	—	—	10	—	—	—	—	—	—	—	3 9/32	1	2 3/8	—	—	—	—	50
TQL/TQB/ TQC	10	1	120/240	—	—	52	—	—	—	—	—	—	—	3 9/32	1	2 3/8	—	—	—	—	50
		2	120/240	—	—	—	52	—	—	—	—	—	—	3 9/32	1	2 3/8	—	—	—	—	25
		3	240	—	—	—	—	—	—	—	—	—	—	3 9/32	2	2 3/8	—	—	—	—	15
THQL ¹	15-70	1	120/240	—	—	10	—	—	—	—	—	—	—	3 9/32	3	2 3/8	—	—	—	—	50
THQB ¹	15-125	2	120/240	—	—	—	10	—	—	—	—	—	—	3 9/32	1	2 3/8	—	—	—	—	25
THQC ¹	15-100	3	240	—	—	—	—	—	—	—	—	—	—	3 9/32	2	2 3/8	—	—	—	—	15
THHQB ¹ THHQC ¹	15-70	1	120/240	—	—	22	—	—	—	—	—	—	—	3 9/32	3	2 3/8	—	—	—	—	50
	15-100	2	120/240	—	—	—	22	—	—	—	—	—	—	3 9/32	1	2 3/8	—	—	—	—	25
		3	240	—	—	—	—	—	—	—	—	—	—	3 9/32	2	2 3/8	—	—	—	—	15
THHQL ¹	15-70	1	120/240	—	—	22	—	—	—	—	—	—	—	3 9/32	3	2 3/8	—	—	—	—	50
	15-125	2	120/240	—	—	—	22	—	—	—	—	—	—	3 9/32	1	2 3/8	—	—	—	—	25
	15-100	3	240	—	—	—	—	—	—	—	—	—	—	3 9/32	2	2 3/8	—	—	—	—	15
TXQL ¹ TXQB ¹ TXQC ¹	15-30	1	120/240	—	—	65	—	—	—	—	—	—	—	3 9/32	3	2 3/8	—	—	—	—	50
		2	120/240	—	—	—	65	—	—	—	—	—	—	3 9/32	1	2 3/8	—	—	—	—	25
		3	240	—	—	—	—	—	—	—	—	—	—	3 9/32	2	2 3/8	—	—	—	—	15
TQD ¹	100-225	2	240	—	—	10	10	—	—	—	—	—	—	6 9/16	3	2 5/8	2 7/16	2 7/16	—	27/32	1
	100-225	3	240	—	—	—	10	—	—	—	—	—	—	6 9/16	4 1/8	2 5/8	2 7/16	2 7/16	11/16	27/32	1
THQD ¹	100-225	2	240	—	—	22	22	—	—	—	—	—	—	6 9/16	3/4	2 5/8	2 7/16	2 7/16	—	27/32	1
	100-225	3	240	—	—	—	22	—	—	—	—	—	—	6 9/16	1 1/2	2 5/8	2 7/16	2 7/16	11/16	27/32	1
TJD	250-400	2	240	—	—	22	22	—	—	—	—	10	—	10 1/8	3	3 13/16	3 13/16	3 13/16	1 3/8	1 3/16	1
		3	240	—	—	—	22	—	—	—	—	—	—	10 1/8	8 1/4	3 13/16	3 13/16	3 13/16	1 3/8	1 3/16	1

Ground Fault, Equipment Ground Fault, Arc Fault and Dual Function, Fixed Thermal Trip

THQL THQC THQB GFT, GFEP	15-30	1	120	—	10	—	—	—	—	—	—	—	—	3 9/32	1	2 3/8	—	—	—	—	10
		2	120/240	—	—	10	—	—	—	—	—	—	—	3 9/32	2	2 3/8	—	—	—	—	10
THHQL THHQB GFT	15-20	1	120	—	22	10	—	—	—	—	—	—	—	3 9/32	1	2 3/8	—	—	—	—	10
THQB THQC THQL ...AF2, DF	15-20	1	120/240	—	—	—	—	—	—	—	—	—	—	3 9/32	1	2 3/8	—	—	—	—	10
THHQB ...AF2, DF THHQL		1	120/240	—	—	22	—	—	—	—	—	—	—	3 9/32	1	2 3/8	—	—	—	—	10


¹UL listed as HACR (heating, air conditioning and refrigeration).

²Not UL listed.

Q-Line Circuit Breakers

Bolt-on Circuit Breakers

240V Class



THQB2115

TQB, THQB 120/240 Vac

# of Poles	Ampere Rating	Wire Range ¹	120/240 Vac Interrupting Rating	Product Number
1	10	14-8 Cu/12-8 Al	5kA	TQB1110 ³
1	15	14-8 Cu/12-8 Al	10kA	THQB1115 ²
1	20	14-8 Cu/12-8 Al	10kA	THQB1120 ²
1	25	14-8 Cu/12-8 Al	10kA	THQB1125
1	30	14-8 Cu/12-8 Al	10kA	THQB1130
1	35	8-3 Cu/8-3 Al	10kA	THQB1135
1	40	8-3 Cu/8-3 Al	10kA	THQB1140
1	45	8-3 Cu/8-3 Al	10kA	THQB1145
1	50	8-3 Cu/8-3 Al	10kA	THQB1150
1	60	8-3 Cu/8-3 Al	10kA	THQB1160
1	70	6-1/0 Cu/4-1/0 Al	10kA	THQB1170

TQB, THQB 120/240 Vac, Internal Common Trip

# of Poles	Ampere Rating	Wire Range ¹	120/240 Vac Interrupting Rating	Product Number
2	10	14-8 Cu/12-8 Al	5kA	TQB2110 ³
2	15	14-8 Cu/12-8 Al	10kA	THQB2115
2	20	14-8 Cu/12-8 Al	10kA	THQB2120
2	25	14-8 Cu/12-8 Al	10kA	THQB2125
2	30	14-8 Cu/12-8 Al	10kA	THQB2130
2	35	8-3 Cu/8-3 Al	10kA	THQB2135
2	40	8-3 Cu/8-3 Al	10kA	THQB2140
2	45	8-3 Cu/8-3 Al	10kA	THQB2145
2	50	8-3 Cu/8-3 Al	10kA	THQB2150
2	60	8-3 Cu/8-3 Al	10kA	THQB2160
2	70	6-1/0 Cu/4-1/0 Al	10kA	THQB2170
2	80	6-1/0 Cu/4-1/0 Al	10kA	THQB2180
2	90	6-1/0 Cu/4-1/0 Al	10kA	THQB2190
2	100	6-1/0 Cu/4-1/0 Al	10kA	THQB21100

TQB, THQB 240 Vac, Internal Common Trip

# of Poles	Ampere Rating	Wire Range ¹	240 Vac Interrupting Rating	Product Number
2	10	14-8 Cu/12-8 Al	5kA	TQB22010 ³
2	15	14-8 Cu/12-8 Al	10kA	THQB22015
2	20	14-8 Cu/12-8 Al	10kA	THQB22020
2	25	14-8 Cu/12-8 Al	10kA	THQB22025
2	30	14-8 Cu/12-8 Al	10kA	THQB22030
2	35	8-3 Cu/8-3 Al	10kA	THQB22035
2	40	8-3 Cu/8-3 Al	10kA	THQB22040
2	45	8-3 Cu/8-3 Al	10kA	THQB22045
2	50	8-3 Cu/8-3 Al	10kA	THQB22050
2	60	8-3 Cu/8-3 Al	10kA	THQB22060
2	70	6-1/0 Cu/4-1/0 Al	10kA	THQB22070
2	80	6-1/0 Cu/4-1/0 Al	10kA	THQB22080
2	90	6-1/0 Cu/4-1/0 Al	10kA	THQB22090
2	100	6-1/0 Cu/4-1/0 Al	10kA	THQB22100
3	10	14-8 Cu/12-8 Al	5kA	TQB32010 ³
3	15	14-8 Cu/12-8 Al	10kA	THQB32015
3	20	14-8 Cu/12-8 Al	10kA	THQB32020
3	25	14-8 Cu/12-8 Al	10kA	THQB32025
3	30	14-8 Cu/12-8 Al	10kA	THQB32030
3	35	8-3 Cu/8-3 Al	10kA	THQB32035
3	40	8-3 Cu/8-3 Al	10kA	THQB32040
3	45	8-3 Cu/8-3 Al	10kA	THQB32045
3	50	8-3 Cu/8-3 Al	10kA	THQB32050
3	60	8-3 Cu/8-3 Al	10kA	THQB32060
3	70	6-1/0 Cu/4-1/0 Al	10kA	THQB32070
3	80	6-1/0 Cu/4-1/0 Al	10kA	THQB32080
3	90	6-1/0 Cu/4-1/0 Al	10kA	THQB32090
3	100	6-1/0 Cu/4-1/0 Al	10kA	THQB32100

¹Solid or stranded for 14-10 AWG.

²UL listed as SWD (Switching Duty) rated. Suitable for switching 120 Vac fluorescent lighting loads.

³Not UL listed.

UL listed HACR (heating, air conditioning and refrigeration).