

WIREMOLD® Steel Raceway

Two-Piece Steel Surface Raceway

Available Factory Prewired

3000® Series Raceway provides wiring capacities for small to medium size installations. Power, communication, or A/V devices can be wired into the raceway for a flush appearance

satisfying both aesthetic and functional requirements.

3000 Series Raceway is ideally suited for wiring applications in frequently changing environments such as labs, hospitals and other industrial applications.



3000 Series Raceway shown utilizing data inserts and electrical devices.



3000 Series Single Channel Raceway has an overlapping cover allowing easy installation and future changes.

FEATURES & BENEFITS

- Entrance knockouts spaced at regular intervals along length of base. Allows power wiring, communication, or A/V cables to be brought in at a convenient point.
- Mounts easily on walls, modular furniture, under raised floors, or over ceiling. Speeds installation; provides flexibility to bring wiring to points of use.
- Removable cover. Provides access to wiring.
- Accommodates a variety of receptacles, three-pole circuit breaker housings, and other protective devices. Provides flexibility for sophisticated wiring systems.
- Complete line of fittings. Provides a complete wiring solution and allows for interconnection between raceway systems.
- Available prewired. Manufactured to specified job site lengths, raceway comes electrically prewired, ready to install. Jobs can be packaged by room, area, floor, or building and shipped per your job site requirements.
- Electrical device identification for prewired raceway. See page six for labeling options. Eliminates guesswork or time-consuming circuit tracing and speeds additions and renovations.

- Compatible with A/V devices by using 5507 Series Faceplates.
- Gray baked enamel and ivory ScuffCoat™ finish. Durable ivory ScuffCoat finish makes a scratch resistant surface.
- Base and cover cutters. Manually operated cutters are lightweight and portable. Cutters offer labor savings for any size job and maintain a factory clean and square cut.
- Datacom connectivity options. Accepts industry standard and proprietary devices from a wide range of manufacturers to provide a seamless and aesthetically pleasing interface for voice, data, audio, and video applications at the point of use.
- UL Listed factory multioutlet assemblies. Listed by Underwriters Laboratories Inc. Multioutlet assemblies file number E15191 Guide (PVGT)/ Fittings file number E41751 Guide (RJPR).
- UL5 and ADA compliant. Raceway and fittings meet UL5 specifications and can be installed in conformance with ADA requirements.
- UL Listed and CSA Certified raceway. Listed by Underwriters Laboratories Inc. Raceway file number E4376 Guide (RJBT)/ Fittings file number E41751 Guide (RJPR) CSA Certified LR350.



Download this product's PEP ecopasport® environmental product declaration at www.legrand.us/resources-and-downloads. This declaration conforms with ISO 14025 and 14040 and is in alignment with EN 15804.

3000 Series Raceway Ordering Information (continued) Catalog No./Item **Description/Specifications** Catalog No./Item **Description/Specifications** G3000WC Wire Clip (Plated) - For holding V3010AE Entrance End - For connecting (25mm) conductors in place. G3010AE to 1/2" conduit and armored cable connectors. 1/2" trade size KO on end and each side. May be 1 3/8" 2 3/4" (70mm) (37mm) connected to conduit boxes by 5/8" using 1/2" (12.7mm) chase nipple. (16mm) (not included) G3001 Coupling (Galvanized Steel **Unpainted)** – For joining lengths 3 7/16" of 3000 Series Raceway. 1 3/8" 5/8" (87mm) (35mm) (16mm) G3010B Blank End – For closing open (57mm) end of 3000 Series Raceway. Has V3010B 2 1/8" concentric 1/2" and 3/4" G3001A (54mm) **Rigid Inside Coupling** trade size KOs. (Galvanized Steel Unpainted) -For joining lengths of 3000 Series 11/16" (17.5mm) Raceway when added rigidity is required, i.e. raceway 1 7/8" 6" suspended overhead. (48mm) (152mm) G3010C Entrance End – For connecting G3003 Supporting Clip – For supporting V3010C to rigid or flexible conduit. lengths of 3000 Series Raceway 2 1/81 Concentric 1/2", 3/4", and 1" at any point. Mount with #8 flat (54mm) trade size KOs on end and head fastener. Has set screw for (51mm) each side. locking to raceway. 2 13/16 1 (25mm) 1 3/8" 3/4" (108mm) (19.1mm) 1 1/16" (35mm) (27mm) G3006E/V3006E Cover Clip - For covering G3011E 90° Flat Elbow - For right angle uneven cut joint of 3000 Series V3011E turns on same surface. 2 13/16" Raceway Cover. (71mm) 6" (152mm) (102mm) ea. leg 3/41 (19.1mm) G3014C Wall Box Connector - For G3007C 🙅 **Device Bracket** – For mounting V3014C connecting from flushed-in standard single-gang devices 3 9/321 wall box. 8" (with 3.3" (83.82mm) mounting (83mm) (203mm) straps), Activate Connectivity inserts and faceplates. Can be used with commercially available 2 3/4" (70mm) flush plate (not furnished). 2 7/81 4 1/2" (114mm) G3015E Tee - For branches at right angles. G3008C C-Hanger - For suspending 3000 V3015E Couplings furnished. Series Raceway from structural (203mm) ceiling. Designed for use with 3/8" (9.5mm) threaded rod. Use one 5 5/16" hanger at least every 4 feet (1.2 m) of length. 10 1/4 4 1/8" (105mm)

*Add C prefix to denote Canadian version - CSA Certified.