Molded Case Circuit Breakers

Panelboard Mounting Circuit Breakers

Arc-Fault Circuit Interrupters (AFCI)

AFCI's detect arcing faults (an unintentional arcing condition in a circuit) that standard circuit breakers are unable to detect. The device is intended to mitigate the effects of arcing faults by functioning to de-energize the circuit when an arcfault is detected.

Combination Type AFCI

Detects all three possible types of arc fault: line-to-ground, line-to-neutral, and series.

Breaker Type	Ampere Rating	10,000 A IR Catalog Number	22,000 A IR Catalog Number	65,000 A IR Catalog Number
BAF2/BAFH2/HBAF2	15	BA115AFC ^①	BA115AFCH■	BA115AFCHH■
1-Pole 120V AC	20	BA120AFC®	BA120AFCH■	BA120AFCHH■
BAF/BAFH	15	B215AFC [®]	B215AFCH■	_
2-Pole 120/240V AC	20	B220AFC ^①	B220AFCH■	_

Dual Function AFCI/GFCI

The Dual Function Circuit Breaker combines Combination Type AFCI and GFCI, protecting against both Arc Faults and (5mA) Ground Faults. The device includes the Self Test feature, making it the first in class in electrical safety for homeowners.

BFGA2/BFGAH2/	15	B115DF	B115DFH■	B115DFHH■
HBFGA2 1-Pole 120V AC	20	B120DF	B120DFH■	B120DFHH■

Ground-Fault Circuit Interrupters (GFCI)

Provides Class A (5mA) ground fault protection. Intended for personnel protection. De-energizes the circuit for all ungrounded conductors of the circuit.

Breaker	Amp	10k A IR	22k A IR	65k A IR
Type	Rating	Cat. No.	Cat. No.	Cat. No.
BLF2/ BLHF2 1-Pole 120V AC Bolt-On	15 20 25 30	BF115A ^① BF120A ^① BF125A BF130A	BF115AH ^① BF120AH ^① BF125AH BF130AH	BF115AHH■ BF120AHH■ BF125AHH■ BF130AHH■
BLF/	15	BF215 A	BF215AH■	
BLHF	20	BF220 A	BF220AH	
2-Pole	30	BF230 A	BF230AH	
120/240V	40	BF240 A	BF240AH■	
AC	50	BF250 A	BF250AH■	
Bolt-On	60	BF260 A	BF260AH■	

Ground Fault Equipment Protection (30mA)

Provides protection of equipment from damaging line-to-ground faults currents. De-energizes the circuit for all ungrounded conductors of the circuit.

Breaker	Amp	10k A IR	22k A IR
Type	Rating	Cat. No.	Cat. No.
BLE/ BLEH 1-Pole, 120V AC Bolt-On	15 20 30	BE115 ^① BE120 ^① BE130	BE115H■ ^① BE120H■ ^① BE130H■
BLE/	15	BE215	BE215H■ BE220H■ BE230H■ BE240H■ BE250H■ BE250H■
BLEH	20	BE220	
2-Pole	30	BE230	
120/240V	40	BE240	
AC	50	BE250	
Bolt-On	60	BE260	

• UL Listed

• HACR Rated

Selection













BAF2/BLF2/BLE Accessories

Description	Catalog Number
Padlocking Device 1-Pole	ECPLD1
Padlocking Device 2-Pole	ECPLD2
Handle Block	ECBX231M

Wiring Diagrams





Built to order. Allow 8 -10 weeks for delivery.

UL Listed as SWD (Switching Duty) Rated, suitable for 120V AC Fluorescent Lighting.