



T6.5



A19



R14 Inter



R14



T8



T10

GENERAL PURPOSE LAMPS

Watts	Bulb	Base	Product Number	Symbols & Footnotes	Ordering Abbreviation	Volts	Pkg Qty	Description	Class & Filament	Avg Rated Life(hrs)	Lumens Beam Angle CBCP	LCL (in)	MOL (in)
20	T6.5	DC Bayonet	18144		20T6.5DC/IF	120	60	Inside Frost Exit Lamp	B, C-8	10000	92		5.56
		Intermediate	18143		20T6.5/IF	120	60	Inside Frost Exit Lamp	B, C-8	10000	92		5.50
25	A19	Med	11090		25A/RS	120	120	Inside Frost Rough Service	B, C-17	1000	210	2.50	3.94
			11092		25A/RS	130	120	Inside Frost Rough Service	B, C-17	1000	210	2.50	3.94
			10562		25A/W/RP	120	24	Soft White	C, C-9	2500	160	2.50	3.94
			10644		25A	120	120	Standard Frost	B, C-9	2500	190	2.50	3.94
			10634		25A/RP	120	24	Standard Frost	B, C-9	2500	190	2.50	3.94
			10645	^{136,146}	25A @120_volts, approximate 22 watts, 130 lumens, 6250 hours	130	120	Standard Frost	B, C-9	2500	180	2.50	3.94
			11285		25A	230	120	Standard Frost	B, C-17	1000	205	2.50	3.94
			11289		25A	277	120	Standard Frost	B, C-17	1000	187	2.50	3.94
		Med Brass	10693		25A/CL	120	120	Clear	B, C-9	2500	190	2.50	3.94
			10683		25A/CL/RP	120	24	Clear	B, C-9	2500	190	2.50	3.94
			10694	^{136,146}	25A/CL @120_volts, approximate 22 watts, 130 lumens, 6250 hours	130	120	Clear	B, C-9	2500	180	2.50	3.94
			11710		25A19/TB/RP	125	6	Transparent Blue	B, C-9	3000		2.50	3.94
			11714		25A19/TG/RP	125	6	Transparent Green	B, C-9	3000		2.50	3.94
			11711		25A19/TO/RP	125	6	Transparent Orange	B, C-9	3000		2.50	3.94
			11712		25A19/TR/RP	125	6	Transparent Red	B, C-9	3000		2.50	3.94
			11713		25A19/TY/RP	125	6	Transparent Yellow	B, C-9	3000		2.50	3.94
			10449		25A	12	120	Standard Frost	B, C-6	1000	385	2.50	3.94
		R14	14793		25R14N	120	60	Reflector Mini Flood	B, CC-2V	1500	132		2.56
			14784		25R14N/RP	120	6	Reflector Mini Flood	B, CC-2V	1500	132		2.56
		Med	14818		25R14/RP	120	6	Reflector Mini Flood	C, CC-2V	1500	132		2.25
T6.5	DC Bayonet		18129		25T6.5/DC	120	60	Clear Scale Illuminator	B, C-8	1000	242		5.56
			18106		25T6.5/DC	130	60	Clear Scale Illuminator	B, C-8	1000	242		5.56
			18117		25T6.5/DC/IF	120	60	Inside Frost Scale Illuminator	B, C-8	1000	225		5.56
		Intermediate	18125		25T6.5	120	60	Clear	B, C-8	1000	242		5.50
			18496		25T6.5/CL/BL/10PK	120	10	Clear	B, C-8	1000	242		5.50
			18495		25T6.5/BL/6PK	120	6	Clear	B, C-8	1000	242		5.50
			18128		25T6.5	130	60	Clear	B, C-8	1000	242		5.50
			18113		25T6.5/IF	120	60	Inside Frost	B, C-8	1000	225		5.50
			18111		25T6.5/IF	130	60	Inside Frost	B, C-8	1000	225		5.50
		Candelabra	18289		25T8C	120	60	Clear Home Appliance	B, C-7A	1000	230	1.50	2.63
			18310		25T8DC	120	60	Clear Home Appliance	B, C-7A	1000	230	1.31	2.63
			18321		25T8DC/BL	120	12	Clear Home Appliance	B, C-7A	1000	230	1.31	2.63
			18316		25T8DC	130	60	Clear Home Appliance	B, C-7A	1000	215	1.31	2.63
T8	DC Bayonet	Intermediate	18359		25T8N	120	60	Clear Home Appliance	B, C-7A	1000	230	1.31	2.63
			18365		25T8N/BL	120	12	Clear Home Appliance	B, C-7A	1000	230	1.31	2.63
			18360		25T8N/BL/1/6	120	6	Clear Home Appliance	B, C-7A	1000	230	1.31	2.63
T10	Med		18510		25T10	120	60	Clear	B, C-8	1000	232		5.63