

Product Type	Item Number	Ordering Abbreviation	Watts	Voltage (V)	Dim (V)	CRI
	61872	UCKIT008TL9SC624INWH	8	120	Yes	>93
Shop Light	61451	LEDSHOP/120/42840/4FT/G2	42	120	—	80
	61452	LEDSHOP/120/30840/3FT	30	120	—	80
Vapor Tight (Clear Lens)	74530	VAPOR1A/025UNVD840/24EC/GR	25	120-277	0-10	80
	74531	VAPOR1A/025UNVD850/24EC/GR	25	120-277	0-10	80
	74532	VAPOR1B/025UNVD840/24EC/GR/D	25	120-277	0-10	80
	74533	VAPOR1B/025UNVD850/24EC/GR/D	25	120-277	0-10	80
	60074	VAPOR1B/025UNVD840/24EC/GR/E	25	120-277	0-10	80
	60075	VAPOR1B/025UNVD850/24EC/GR/E	25	120-277	0-10	80
	74534	VAPOR1B/020UNVD840/48EC/GR	20	120-277	0-10	80
	74535	VAPOR1B/020UNVD850/48EC/GR	20	120-277	0-10	80
	74536	VAPOR1B/020UNVD840/48EC/GR/D	20	120-277	0-10	80
	74537	VAPOR1B/020UNVD850/48EC/GR/D	20	120-277	0-10	80
	60043	VAPOR1B/020UNVD840/48EC/GR/E	20	120-277	0-10	80
	60044	VAPOR1B/020UNVD850/48EC/GR/E	20	120-277	0-10	80
	60045	VAPOR1B/020UNVD840/48EC/GR/DE	20	120-277	0-10	80
	60046	VAPOR1B/020UNVD850/48EC/GR/DE	20	120-277	0-10	80
	74376	VAPOR1B/040UNVD840/48EC/GR	40	120-277	0-10	80
	74377	VAPOR1B/040UNVD850/48EC/GR	40	120-277	0-10	80
	74378	VAPOR1B/040UNVD840/48EC/GR/D	40	120-277	0-10	80
	74379	VAPOR1B/040UNVD850/48EC/GR/D	40	120-277	0-10	80
	74554	VAPOR1B/040UNVD840/48EC/GR/E	40	120-277	0-10	80
	74555	VAPOR1B/040UNVD850/48EC/GR/E	40	120-277	0-10	80
	74556	VAPOR1B/040UNVD840/48EC/GR/DE	40	120-277	0-10	80
	74557	VAPOR1B/040UNVD850/48EC/GR/DE	40	120-277	0-10	80
	74552	VAPOR1A/050HUNVD840/48EC/GR	50	347-480	0-10	80
	74553	VAPOR1A/050HUNVD850/48EC/GR	50	347-480	0-10	80
	60376	VAPOR1B/050HUNVD840/48EC/GR/D	50	347-480	0-10	80
	60377	VAPOR1B/050HUNVD850/48EC/GR/D	50	347-480	0-10	80
	60047	VAPOR2B/040UNVD840/48EC/GR	40	120-277	0-10	80
	60048	VAPOR2B/040UNVD850/48EC/GR	40	120-277	0-10	80
	60049	VAPOR2B/040UNVD840/48EC/GR/D	40	120-277	0-10	80
	60050	VAPOR2B/040UNVD850/48EC/GR/D	40	120-277	0-10	80
	60355	VAPOR1B/065UNVD840/96EC/GR	65	120-277	0-10	80
	60356	VAPOR1B/065UNVD850/96EC/GR	65	120-277	0-10	80
	60357	VAPOR1B/065UNVD840/96EC/GR/D	65	120-277	0-10	80
	60358	VAPOR1B/065UNVD850/96EC/GR/D	65	120-277	0-10	80
	60359	VAPOR1B/065UNVD840/96EC/GR/E	65	120-277	0-10	80

*LPW per LM79 report

†Indicates that the product is discontinued with inventory.

(MTO) = Made to Order

Note: All luminaires and retrofit kits are UL/ETL, FCC, RoHS and backed by a 5 year warranty

Dimensions	Lumens	LPW*	LED L ₇₀ Lifetime (h)	Dry/ Wet/ Damp	Replaces Traditional Equivalent Up To	Options **	DLC (Std/Prem) & ENERGY STAR®
24" x 1.65" x 0.55"	540	67	50,000	—	—	—	E-STAR
47.7" x 4.25" x 1.22"	4,200	100	50,000	Dry	2 x 32W T8	—	E-STAR
35.7" x 2.48" x 1.33"	3,000	100	50,000	Dry	2 x 28W T8	—	E-STAR
24.9" x 4.0" x 3.3"	3,100	135	84,000	IP65	70W HPS	—	Prm
24.9" x 4.0" x 3.3"	3,100	137	84,000	IP65	70W HPS	—	Prm
24.9" x 4.0" x 3.3"	3,100	135	84,000	IP65	70W HPS	D	Prm
24.9" x 4.0" x 3.3"	3,100	137	84,000	IP65	70W HPS	D	Prm
24.9" x 4.0" x 3.3"	3,100	135	84,000	IP65	70W HPS	E	Prm
24.9" x 4.0" x 3.3"	3,100	137	84,000	IP65	70W HPS	E	Prm
48.5" x 3.4" x 3.3"	2,600	127	84,000	IP65	70W HPS	—	Prm
48.5" x 3.4" x 3.3"	2,600	128	84,000	IP65	70W HPS	—	Prm
48.5" x 3.4" x 3.3"	2,600	127	84,000	IP65	70W HPS	D	Prm
48.5" x 3.4" x 3.3"	2,600	128	84,000	IP65	70W HPS	D	Std
48.5" x 3.4" x 3.3"	2,500	130	84,000	IP65	70W HPS	E	Prm
48.5" x 3.4" x 3.3"	2,500	130	84,000	IP65	70W HPS	E	Prm
48.5" x 3.4" x 3.3"	2,500	130	84,000	IP65	70W HPS	DE	Prm
48.5" x 3.4" x 3.3"	2,500	130	84,000	IP65	70W HPS	DE	Prm
48.1" x 4.0" x 3.3"	5,300	139	84,000	IP65	70W MH	—	Prm
48.1" x 4.0" x 3.3"	5,300	137	84,000	IP65	70W MH	—	Prm
48.1" x 4.0" x 3.3"	5,400	140	84,000	IP65	70W MH	D	Prm
48.1" x 4.0" x 3.3"	5,400	137	84,000	IP65	70W MH	D	Prm
48.1" x 4.0" x 3.3"	5,300	139	84,000	IP65	70W MH	E	Prm
48.1" x 4.0" x 3.3"	5,300	137	84,000	IP65	70W MH	E	Prm
48.1" x 4.0" x 3.3"	5,400	140	84,000	IP65	70W MH	DE	Prm
48.1" x 4.0" x 3.3"	5,400	137	84,000	IP65	70W MH	DE	Prm
48.1" x 4.0" x 3.3"	5,700	111	84,000	IP65	70W MH	—	—
48.1" x 4.0" x 3.3"	5,700	111	84,000	IP65	70W MH	—	—
48.1" x 4.0" x 3.3"	5,700	111	84,000	IP65	70W MH	D	—
48.1" x 4.0" x 3.3"	5,700	111	84,000	IP65	70W MH	D	—
49.1" x 4.8" x 3.3"	5,300	139	84,000	IP67	70W MH	—	Prm
49.1" x 4.8" x 3.3"	5,300	137	84,000	IP67	70W MH	—	Prm
49.1" x 4.8" x 3.3"	5,300	139	84,000	IP67	70W MH	D	Prm
49.1" x 4.8" x 3.3"	5,300	137	84,000	IP67	70W MH	D	Prm
96" x 4.0" x 3.3"	8,750	135	84,000	IP65	250W MH	—	Prm
96" x 4.0" x 3.3"	8,750	135	84,000	IP65	250W MH	—	Prm
96" x 4.0" x 3.3"	8,750	135	84,000	IP65	250W MH	D	Prm
96" x 4.0" x 3.3"	8,750	135	84,000	IP65	250W MH	D	Prm
96" x 4.0" x 3.3"	8,750	135	84,000	IP65	250W MH	E	Prm

Options Abbreviations: **D = Motion and Daylight Sensor, **E** = Emergency Battery Back-up, **ER** = Emergency Back-up Battery Ready, **DE** = Motion/Daylight Sensor + Emergency Battery Back-up, **IoT** = Internet of Things Ready, **P** = Photocontrol, **PE** = Photocontrol + Emergency Battery Back-up, **W** = Whip, **10kv** = 10kv surge protection, **165** = 165° distribution