ULTRA LED™ Glass PAR16 Lamps





SYLVANIA ULTRA LED PAR16 lamps last 12 times longer than halogen PAR16 lamps and are a high quality replacement for 50W halogen PAR16 lamps. They are free of UV and IR radiation, minimizing discoloration and fading of materials. These LED lamps will reduce energy and maintenance cost when compared with conventional halogen light sources.

Key Features & Benefits

- True glass housing that mimics halogen PAR16
- Long life: rated up to 25,000 hours (L₇₀)
- Available in 3000K color temperature
- UV and IR free
- Suitable for damp locations
- RoHS compliant

- Available in medium and GU10 base
- Dimmable down to 10%
- Mercury and lead free
- Lasts up to 12 times longer than halogen lamps
- No warm-up time, instant-on with full light output and stable color

* Performance may vary depending on dimmer used in application. Please refer to Dimmer Compatibility List (RETRO-DIM) for a list of compatible dimmers or visit www.SYLVANIA.com/LEDRetrofit











Product Offering

Ordering		Beam
Abbreviation	Wattage	Angle
PAR16	6	36°

Application Information

Applications

- Recessed downlighting
- Track lighting
- Wall washers

Market Segments

- Art galleries and museums
- Hospitality
- Offices
- Residential
- Restaurants
- Retail

Application Notes

- Operating temperature range between -4°F and +104°F (-20°C and +40°C)
- 2. Suitable for outdoor use when used in a UL rated fixture where protected from the weather
- 3. Not intended for use with emergency light fixtures or exit lights
- 4. Use in open fixture

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, please see www.svlvania.com/fcc15b



Specification Data

Catalog #	Туре	
Project Comments		
Comments		
Prepared by		

Ordering Information

Item	Ordering	Wattage	Base		Input Voltage	Average Rated		Typical Lumens	СВСР	0.711	Beam	Power	ENERGY
Number	Abbreviation	(W)	Type	Replaces	(V)	Life (hrs.) ¹	CCT ³	(lm) ²	(cd)	CRI4	Angle	Factor	STAR®
78287	LED6PAR16/DIM/830/FL36/GL1/RP	6	Medium	50W	120	25,000	3000K	450	1000	82	36	0.95	Yes
78288	LED6PAR16GU10/DIM/830/FL36/GL1/RP	6	GU10	50W	120	25,000	3000K	450	1000	82	36	0.95	Yes
79287*	LED6PAR16/DIM/830/FL36/GL1/RP	6	Medium	50W	120	25,000	3000K	450	1000	82	35	0.95	Yes
79288*	LED6PAR16GU10/DIM/830/FL36/GL1/RP	6	GU10	50W	120	25,000	3000K	450	1000	82	35	0.95	Yes

SYLVANIA submits most lamps for ENERGY STAR testing. Early qualification for ENERGY STAR lamps begin at 25,000 hours (L_{70}) regardless that the design of the lamp is manufactured for a greater life expectancy. As the lamps pass ENERGY STAR qualifications, manufacturers are able to increase rated life as dictated by ENERGY STAR guidelines becoming either provisionally qualified or fully qualified. Please visit EnergyStar.gov for more information about testing requirements for ENERGY STAR qualified products.

*Phase out 79287 and 79288

Ordering Guide

LED	6	PAR16	1	GU10	1	DIM	1	830	1	FL	36
LED	Wattage:	Lamp Type:		Base		Dimmable		CRI, CCT:		Beam Type:	Beam
Lamps and	6	PAR16		Type:				830: 80+	,	FL: Flood	Angle:
Retrofits				GU10				3000K CC	T		36°

Energy Savings

Basic Product	LED	Similar	Halogen	Watts	Energy	LED Life vs.
Description	Life (hrs.)	Halogen	Life (hrs.)	Saved	Savings*	Halogen
LED6PAR16	25.000	50PAR16	3.000	44	\$121	8.3X

^{*}Energy savings over life of lamp calculated at \$0.11/kWh

Lamp Dimensions

LED6PAR16 LED6PAR16/GU10	(A) MOL (inches) 2.9 2.1	(B) Diameter (inches) 1.9 1.9	B	B A
			LED6PAR16	LED6PAR16/GU10

Sample Specification

Lamps shall be SYLVANIA ULTRA LED PAR16 with a 25,000 hour average rated life. Lamps shall be energy efficient, UV & IR free. Should have a beam angle of 36 degrees.

LEDVANCE LLC 200 Ballardvale Street Wilmington, MA 01887 USA Phone 1-800-LIGHTBULB (1-800-544-4828) www.sylvania.com

SYLVANIA and LEDVANCE are registered trademarks.

All other trademarks are those of their respective owners.

Licensee of product trademark SYLVANIA in general lighting.

Specifications subject to change without notice.







^{1.} Hours lifetime with 70% lumen maintenance 2. Thermally stable typical lumens (±10%) 3. Thermally stable typical CCT (±10%) 4. CRI – Color Rendering Index