

HALO CANLESS DIRECT MOUNT

HLB Downlight
CANLESS DIRECT MOUNT

- Ultra-thin prismatic LED lens downlight with remote driver/junction box
- Installs into drywall/suspended ceiling (no j-box or housing required)
- 5 field-selectable CCT: 2700K, 3000K, 3500K, 4000K, 5000K; 90 CRI
- Install from below the ceiling in as little as 3-1/2-inch plenum height
- Insulated Ceiling (IC) rated and Non-IC rated applications



Catalog Number	Description	Finish	Replaces Up To	Selectable CCT	Voltage	Lumens	Watts	UPC	ENERGY STAR ID
HLB3059FS1EMWR	3" Module, Round	White	40W INC	2700K-5000K	120V	500	9	080083151301	N/A
HLB3S059FS1EMWR	3" Module, Square	White	40W INC	2700K-5000K	120V	500	9	080083151325	2336938
HLB4SP069FS1EMWR	4" Module, Square	White	65W INC	2700K-5000K	120V	600	10	080083909667	2347583
HLB4069FS1EMWR	4" Module, Round	White	65W INC	2700K-5000K	120V	752	12	080083848140	2322243
HLB4069FSE010MWR	4" Module, Round	White	60W INC	2700K-5000K	120-277V	750	11	080083912261	2351376
HLB4S069FSE010MWR	4" Module, Square	White	60W INC	2700K-5000K	120-277V	725	11	080083912308	2351374
HLB6099FS1EMWR	6" Module, Round	White	65W INC	2700K-5000K	120V	1103	16	080083848164	2322242
HLB6S099FS1EMWR	6" Module, Square	White	65W INC	2700K-5000K	120V	1103	12	080083863389	2331663
HLB6099FSE010MWR	6" Module, Round	White	75W INC	2700K-5000K	120-277V	1061	15	080083912285	2351377
HLB6S099FSE010MWR	6" Module, Square	White	75W INC	2700K-5000K	120-277V	1050	15	080083912322	2351375
HLB8169FS1EMWR	8" Module, Round	White	90W INC	2700K-5000K	120V	1600	21	080083150601	2358047
HLB8LS9FSE010MWR	8" Module, Round	White	150W INC	2700K-5000K	120-277V	2400	31	080083083367	2358045
HLB12LS9FSE010MWR	12" Module, Round	White	150W INC	2700K-5000K	120- 277V	2400	32	080083088782	N/A

HLB Slim Edge Downlight
CANLESS DIRECT MOUNT

- Smooth LED lens downlight with remote driver/junction box
- Installs into drywall/suspended ceiling (no j-box or housing required)
- 5 field-selectable CCT: 2700K, 3000K, 3500K, 4000K, 5000K; 90 CRI
- Install from below the ceiling in as little as 1-1/2 inch plenum height
- Insulated Ceiling (IC) rated and Non-IC rated applications



Catalog Number	Description	Finish	Replaces Up To	Selectable CCT	Voltage	Lumens	Watts	UPC	ENERGY STAR ID
HLBPH4069FS1EMWR	4" Module, Round	White	65W INC	2700K-5000K	120V	830	10	080083190003	2385132
HLBPH6099FS1EMWR	6" Module, Round	White	65W INC	2700K-5000K	120V	1100	14	080083190027	2385133

HALO CANLESS DIRECT MOUNT

HLB Lite Downlight
CANLESS DIRECT MOUNT

- Ultra-thin LED lens downlight with remote driver/junction box
- Installs into drywall/suspended ceiling (no j-box or housing required)
- Features a round polymer trim and smooth lens
- 3 field-selectable CCT: 2700K, 3000K, 3500K, 4000K, 5000K; 90 CRI
- Install from below the ceiling in 3/8-inch to 5/8-inch thick ceilings



Catalog Number	Description	Finish	Replaces Up To	Selectable CCT	Voltage	Lumens	Watts	UPC	ENERGY STAR ID
HLBSL4069FS231EMWR	4" Module, Round	White	60W INC	2700K - 3500K	120V	753	10	080083912346	2349484
HLBSL4069FS351EMWR	4" Module, Round	White	60W INC	3000K - 5000K	120V	716	10	080083916368	2349485
HLBSL4069FS461EMWR	4" Module, Round	White	60W INC	4000K - 6000K	120V	771	10	080083912384	2388764
HLBSL6099FS231EMWR	6" Module, Round	White	75W INC	2700K - 3500K	120V	954	13	080083912360	2349475, 2349476, 2349477
HLBSL6099FS351EMWR	6" Module, Round	White	75W INC	3000K - 5000K	120V	940	13	080083916382	2349478, 2349479, 2349480
HLBSL6099FS461EMWR	6" Module, Round	White	75W INC	4000K - 6000K	120V	1015	12	080083912407	2388798

RL Baffle Trim Downlight
CANLESS DIRECT MOUNT

- 4 and 6-inch regressed LED lens downlights with remote driver/junction box
- Installs into drywall/suspended ceiling (no j-box or housing required)
- 5 field-selectable CCT: 2700K, 3000K, 3500K, 4000K, 5000K; 90 CRI
- Can be installed in ½-inch to 1 ¼-inch thick ceilings
- Insulated ceiling (IC) and non-IC rated; Dimmable to 5% (120V dimmers)



Catalog Number	Description	Finish	Replaces Up To	Selectable CCT	Voltage	Lumens	Watts	UPC	ENERGY STAR ID
RL4069S1EWHDM	4" Direct Mount Module	White	65W INC	2700K-5000K	120V	652	9	080083858101	2325604
RL4069S1EWHDMR	4" Direct Mount Module	White	65W INC	2700K-5000K	120V	600	9	080083858064	2388493
RL6069S1EWHDM	6" Direct Mount Module	White	65W INC	2700K-5000K	120V	719	9	080083858125	2325603

RL Night Light Downlight
CANLESS DIRECT MOUNT

- 4 and 6-inch LED night light downlight with remote driver/junction box
- Installs into drywall/suspended ceiling (no j-box or housing required)
- 2" depth great for use in ultra-shallow plenum spaces
- Two modes: downlight mode and nightlight mode
- 5 field-selectable CCTs: 2700K, 3000K, 3500K, 4000K, 5000K; 90 CRI



Catalog Number	Description	Finish	Replaces Up To	Selectable CCT	Voltage	Lumens	Watts	UPC	ENERGY STAR ID
RL4069NLWHDMMR	4" Module, Round	White	65W INC	2700K - 5000K	120V	845	9	080083183005	2381590
RL6069NLWHDMMR	6" Module, Round	White	75W INC	2700K - 5000K	120V	1115	11	080083183029	2381581