

Legrand 20GB618 Steel Plugmold® Multioutlet System

Part No. V20GB618



6' Plugmold Multioutlet System with 4 single outlets 18 inches apart, GB

Features & Benefits

Steel Raceway. Provides superior strength for any dry location installation.

Compact, low profile appearance. Requires minimal space.

Available in Ivory ScuffCoat or gray baked enamel finish. The durable ScuffCoat provides a durable, scratch-resistant finish while the gray baked enamel compliments the décor or can be painted.

Full range of fittings. Provides a complete wiring solution.

Single-and-dual-gang boxes. Wire devices into the raceway system or protect a Plugmold® strip with a surge or GFCI device.

Factory wired Plugmold® sections available in 3° , 5° , and 6° lengths with 15A receptacles installed in cover. Ideal for short runs requiring additional outlets in electrically busy areas.

Single, alternating circuit, and isolated ground receptacles. Meets virtually any job requirement.

Customization available. All products can be modified to accommodate virtually any application.

Choice of receptacle spacing. Center spacing between receptacles of 6", 9", 12", and 18".

Snapicoil harnesses of prewired receptacles in 48' and 50'. Eliminates multiple splicing, speeding up

Snapicoil harnesses offer a choice of receptacle spacing. Center spacing between receptacles of 12". 18" and 30"

installation on long runs.

This product meets the material restrictions of RoHS.

Specifications

General Info

UPC Number	786776093346	Country Of Origin	United States
Product Line	Wiremold	Application Sector	Commercial
Туре	Plugmold	Number of Receptacles	4
Standard	cULus Listed Raceway: File E4376 Guide RJBT. Fittings: File E41751 Guide RJPR. Base & Black Cover: Meets Article 386 of NEC. Meets Section 12-600 of CEC.		

Listing Agencies / 3rd Party Agencies

cULus Listed cULus ListingNumber E15191

Buy American Act Compliance

NAFTA Yes

Additional Information

RoHS Conformant

Product Environmental Profile

Technical Information					
Voltage	125 V	Enclosure Type	Steel		
Environmental Conditions	Dry interior locations				