



Industrial grade 20A locking devices

Product description

4-pole, 5-wire grounding
20A, 3ØY 120/208V/AC
NEMA L21-20



AHL2120PF



IGL2120R



AHL2120FI

Industrial grade plugs & connectors



Rating A	V/AC	NEMA	Description	Cord diameter	Color	Plug catalog no.	Connector catalog no.		
20	120/ 208	L21-20	3ØY ultra grip straight body	0.38-1.16" (9.5-29.4mm)	BK & W	☐ AHL2120P	☐ AHL2120C	•	•
			3ØY ultra grip straight body	0.38-1.16" (9.5-29.4mm)	BK	☐ AHL2120PBK	☐ AHL2120CBK	•	•
			3ØY ultra grip flat cable, straight body	Max. 5-wire #10 AWG flat cable	GY	☐ AHL2120PF ^A	☐ AHL2120CF ^A	•	•

^ANot UL Listed

Industrial grade receptacles



Rating A	V/AC	NEMA	Description	Color	Single receptacle		
20	120/ 208	L21-20	3ØY standard industrial	BK	☐ AHL2120R	•	•
			3ØY isolated ground	RN	☐ IGL2120R*	•	•

*Not Fed Spec

Industrial grade flanged inlets



Rating A	V/AC	NEMA	Description	Color	Flanged inlet		
20	120/ 208	L21-20	3ØY standard industrial	BK	☐ AHL2120FI	•	•

Industrial grade flanged outlets



Rating A	V/AC	NEMA	Description	Color	Flanged outlet		
20	120/ 208	L21-20	3ØY standard industrial	BK & W	☐ AHL2120FO	•	•

Accessories for L21-20 locking devices

Description	Catalog no.		
Neoprene weather protective boot for 4-W & 5-W plugs	☐ BL1	•	
Neoprene weather protective boot for 4-W & 5-W connectors	☐ BL2	•	
Diecast aluminum single receptacle cover, vertical mount, for FS/FD boxes	☐ 7420	•	•
Glass-filled nylon flanged inlet/outlet cover, vertical mount, for 20A devices	☐ WP2	•	•



BL1



BL2



7420



WP2

Dimensional information:
C-76-C-78

Plug & connector specification information:
L21-20: C-85

Receptacle specification information:
L21-20: C-87

Isolated ground L21-20: C-87

Flanged inlet & flanged outlet specification information:
L21-20: C-89

Color information:

BK (Black), GY (Gray), RN (Orange), W (White)

BK	GY	RN	W
(Black)	(Gray)	(Orange)	(White)

Compliances, specifications and availability are subject to change without notice.



Indicates NAFTA compliant - Page Q-32



RoHS compliant - Page Q-32